Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

SUNDRY NOTICES	3 AND	REPORTS	ON	WELLS
----------------	-------	---------	----	-------

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

NM 53936 6. If Indian, Allottee or Tribe Name

Use "APPLICATION FOR PERMIT—" for such proposals	- 42	
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well Oil X Well Other  2. Name of Operator Giant Exploration & Production Company  3. Address and Telephone No. P.O. Box 2810, Farmington, N.M. 87499 (505)326-3325  4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1500' FSL, 2310' FWL, Sec. 15, T25N, R13W	8. Well Name and No. West Bisti Coal 15 #2 9. API Well No. 30-045-28390 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 11. County or Parish, State San Juan, New Mexico	
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPO		
	TYPE OF ACTION	
Notice of Inten    Abandonment   Recompletion	Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off  Conversion to Injection  Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log torm.)	

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled out from under casing with 6-1/4" bit November 19, 1990. Drilled to TD of 1330'. Ran Compensated Density-Neutron logs with gamma ray. Log tops as follows: Fruitland - 976', Basal Fruitland Coal - 1162', Pictured Cliffs -1204'. Ran 31 jts. (1324.17') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1321.86', PBD at 1279.03'. Cemented casing as follows: Mixed and pumped 75 sks. (154.5 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 70 sks. (82.6 cu. ft.) of Class "B" cement containing 2% CaCl  $_2$  and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500psi for 15 minutes. Test ok. Waiting on completion operations.

14. I hereby certify that the foregoing is true and correct  Signed Title President	ACCEPTED FOR RECORD
(This space for Federal or State office use)  Approved by Title	JAN 17 1991
Conditions of approval, if any:	FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious of translation statements or representations as to any matter within its jurisdiction.