Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

RECEIVED	
BLiff	

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

NM 53936-A

SUNDRY NOTICES AND REPORTS ON WELLS! -3 MILLS 34 Do not use this form for proposals to drill or to deepen or reentry to a different reservoir Use "APPLICATION FOR PERMIT—" for such Optobosals

6. If Indian, Allottee or Tribe Name

	r · r · · · ·	
SUBMIT IN TRIPLICA	TE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Well Well Other		8. Well Name and No.
2. Name of Operator Giant Exploration & Production Company 3. Address and Telephone No.		West Bisti Coal 11 Com # 9. API Well No.
P.O. Box 2810, Farmington, N.M. 87499 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	(505)326-3325	10. Field and Pool, or Exploratory Area Basin Fruitland Coal
1100'FNL, 2510' FEL, Sec. 11, T25N, R13W	to see the second	11. County or Parish, State
CHECK APPROPRIATE BOX(s) TO INDICA	TE NATURE OF NOTICE, REPOR	San Juan, New Mexico T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Subsequent Report FEB1 1 1991. Final Abandonment Notice DIST. 3	Abandonment Recompletion Plugging Back Casing Repair Altering Casing Other Other	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion or, Well
B Describe Proposed or Completed Operations (Clearly state all pertinent details, and o	give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Log form.)

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit December 21, 1990. Drilled to TD of 1400'. Ran Compensated Density-Neutron logs with calliper and gamma ray. Log tops as follows: Fruitland Coal - 1059', Basal Fruitland Coal - 1190', Pictured Cliffs - 1233'. Ran 33 jts. (1397.41') of 4-1/2", 9.5#, J-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1395.01', PBD at 1356.11'. Cemented casing as follows: Mixed and pumped 75 sks. (154 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94 cu. ft.) of Class "B" cement containing 2% CaCl $_2$ and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Waiting on completion operations.

Signed le le President Signed President	PARCORD91
(This space for Federal or State office use)	ACCEPTED FUNTILES
Approved by Title Conditions of approval, if any:	FEBat 0 5 1991
	FARMINGTON RESOURCE AREA

Title 18 U.S.C. Section 1991, makes it a crime for any person knowingly and willfully to make to any department or agency of the Exited Secrets any false, fictibious or traudulent statements or representations as to any matter within its jurisdiction.