Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

## NOO-C-14-20-3598 6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

| Use "APPLICATION FOR PERMIT—" for such proposals  |   |
|---|---|
| SUBMIT IN TRIPLICATE  | 7. If Unit or CA, Agreement Designation   |
| 1. Type of Well  Oil  Well X Well  Other  2. Name of Operator  Giant Exploration & Production Company  3. Address and Telephone No.  P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  2400 FNL, 1820 FEL, Sec. 3, T25N, R11W | 8. Well Name and No. Buena Suerte 3G Com #1 9. API Well No. 30-045-28646 10. Field and Pool, or Exploratory Area Basin Fruitland Coal 11. County or Parish, State San Juan, New Mexico                                  |
| 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR  | I   |
| TYPE OF SUBMISSION TYPE OF ACTION   |   |
| Notice of Intent    Notice of Intent   Abandonment  | Change of Plans  New Construction  Non-Routine Fracturing  Water Shut-Off  Conversion to Injection  Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) |

give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled out from under casing with 6-1/4" bit January 25, 1992. Drilled to TD of 1510'. Ran 34 jts. (1503.23') of 4-1/2", 9.5#, K-55, 8rd, ST&C casing. BakerLoked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on tops of 1st, 3rd, 5th, 7th and 9th jts. Casing set at 1499.72', PBD at 1454.88'. Cemented casing as follows: Mixed and pumped 85 sks. (175.1 cu. ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu. ft.) of Class "B" cement containing 2% CaCl2 and 1/4#/sk. cellophane flakes. Cement circulated to surface. Pressure tested casing to 3500 psi for 15 minutes. Test ok. Spectral log. Log tops as follows: Fruitland - 1222', Basal Fruitland Coal -1332', Pictured Cliffs - 1355'. Waiting on completion operations.

|   |                           | RECEI<br>BLI<br>MAY -8<br>FARMIN |
|---|---------------------------|----------------------------------|
| 14. I hereby certify that the foregoing is true and correct Signed                        | Title Engineering Manager | Dag MA 7 4992                    |
| (This space for Federal or State office use)  Approved by Conditions of approval, if any: | Title                     | ACCENTED FOR RECORD              |
|   |                           | MAY 1.5 1992                     |

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false fictitious or fraudulent statements FARMINGTON RESOURCE AREA or representations as to any matter within its jurisdiction.