35. LIST OF ATTACHMENTS

UNITED STATES SUBMIT IN DUPLICATE. DEPARTMENT OF THE INTERIOR

(Sec other in structions on

FOR APPROVED OMB NO. 1004-0137 Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO. reverse side? BUREAU OF LAND MANAGEMENT NM 31311 WELL COMPLETION OR RECOMPLETION 6. IF INDIAN, ALLOTTEE OR TRIBE NAME Ia. TYPE OF WELL: 7. UNIT AGREEMENT NAME b. TYPE OF COMPLETION: MAR 2 9 1993 DEEP-EN WELL X WORK DACK 8. FARM OR LEASE NAME, WELL NO. 2. NAME OF OPERATOR OIL CON. DIV West Bisti Coal 10 No. 1 Giant Exploration & Production Company 9. API WELL NO. 3. ADDRESS AND TELEPHONE NO. 30-045-28798 P.O. Box 2810, Farmington, NM 87499 (505) 326-3325 10. FIELD AND POOL, OR WILDCAT 4. LOCATION OF WELL (Report location clearly and in accordance with any State requiremente). Basin Fruitland Coal 790' FNL, 790' FEL, Sec. 10, T25N, R13W 11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA At top prod. interval reported below At total depth Sec. 10, T25N, R13W 14. PERMIT NO. DATE ISSUED 12. COUNTY OR PARISH 13. STATE San Juan 15. DATE SPUDDED 16. DATE T.D. REACHED 17. DATE COMPL. (Ready to prod.) 18. ELEVATIONS (DF, RKB, RT, GR, ETC.)* 19. ELEV. CASINGHEAD 10-14-92 10-18-92 11-18-92 6320' GLE 20. TOTAL DEPTH, MD & TVD 21. PLUG, BACK T.D., MD & TVD 22. IF MULTIPLE COMPL., 23. INTERVALS ROTARY TOOLS CABLE TOOLS DRILLED BY 14291 1367 24. PRODUCING INTERVAL(S). OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD) X 25. WAS DIRECTIONAL SURVEY MADE 1263' - 1280' Yes 26. TYPE ELECTRIC AND OTHER LOGS RUN 27. Compensated Density-Neutron logs with caliper & gamma ray WAS WELL CORED No[⇔] 29 CASING RECORD (Report all strings set in well) CASING SIZE/GRADE WEIGHT, LB./FT. DEPTH SET (MD) HOLE SIZE TOP OF CEMENT, CEMENTING RECORD = THUDHA PULLED 131 20# 8-3/4" See Exhibit 4-1/2" 9.5#1409.94 6-1/4''See Exhibit 0 29. LINER RECORD 30. TUBING RECORD SIZE TOP (MD) BOTTOM (MD) SACKS CEMENTS SCREEN (MD) DEPTH SET (MD) SIZE PACKER SET (MD) 1 - 1/2''1267 31. PERFORATION RECORD (Interval, size and number) ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED 1263' - 1280' .40" 68 holes 1263'-1280 Fraced with 5,100# 40/70 Brady Sand, 51,000# 12/20 Brady Sand PRODUCTION DATE FIRST PRODUCTION PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) WELL STATUS (Producing or 03-15-93 Flowing Waiting on PL Conn. DATE OF TEST HOURS TESTED CHOKE SIZE PROD'N. FOR TEST PERIOD OIL-BBL. GAS-MCF. WATER-BBL. GAS-OIL BATIO 1/4" 03-18-93 24 0 18.5 1 N/A FLOW. TUBING PRESS CASING PRESSURE CALCULATED OIL--BBL. GAS-MCF. 24-HOUR BATE WATER--BBL OIL GRAVITY-API (CORR.) 0 18.5 N/A 34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) TEST WITNESSED BY To be sold

36. I hereby certify that the foregoing and attached information is complete and correct as determined from alaCCEPTED'F SIGNED Vice President TITLE *(See Instructions and Spaces for Additional Data on Reverse Side)

ACCEPTED FOR REIGHD

Partition of the state of

FOR BOH INCOME

Top for West Bist. Cod 10#1 A-10-25-13

Fruitland 1080' Basal Fruitland 1265' Coal 1317' Pictured Cliffs 1317'	37. SUMMARY OF POR drill-stem, tests, is recoveries):	ncluding depth i	Show all important zones nterval tested, cushion BOTTOM	SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries): FORMATION TOP BOTTOM DESCRIPTION, CONTENTS, ETC.	38. GEOLOGIC MARKERS NAME MEAS. DEPTH
1 Fruitland 1265' ured Cliffs 1317'	uitland	1080'		-	
Cliffs	μ-	1265'			
		1317'			

WEST BISTI COAL 10 WELL NO. 1
790' FNL, 790' FEL
SECTION 10, TOWNSHIP 25 NORTH, RANGE 13 WEST
LEASE NO. NM 31311
SAN JUAN COUNTY
NEW MEXICO
COMPLETION REPORT
EXHIBIT "A"

CEMENT RECORD

Surface Casing

Mixed and pumped 60 sks. (70.8 cu.ft.) of Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface.

Production Casing -

Mixed and pumped 80 sks. (164.8 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cell-ophane flakes. Tailed in with 80 sks. (164.8 cu. ft.) of Class "B" cement containing 2% CaCl and 1/4#/sk. cellophane flakes. Cement circulated to surface.

74 4

B MAR 24 AM 10: S