Form	3160-5
(June	1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED			
Budget Bureau No. 1004-013:			
Expires: March 31 1003			

5. Lease Designation and Serial No.

NM 31311

SHADDY MOTICES	AND DEDODTE ON WELLS	NM 31311
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals		6. If Indian, Allottee or Tribe Name
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
I. Type of Well Oil Well Well Other		8. Well Name and No.
2. Name of Operator		West Bisti Coal 10 #2
Giant Exploration & Production Company 3. Address and Telephone No.		9. API Well No.
P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325		10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		Basin Fruitland Coal
1850' FSL, 2475' FWL, Sec. 10, T25N, R13W, NMPM		11. County or Parish, State
		San Juan, New Mexico
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	IT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
_	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
Final Abandonment Notice	Casing Repair	Water Shut-Off
La Final Adandonment Notice	Altering Casing X Other Drilling Progress	Conversion to Injection
		Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
Drilled out from under casing with 6-1/4" bit on October 27, 1992. Ran Compensated Density-Neutron logs with caliper and gamma ray. Log tops as follows: Fruitland - 1074', Basal Fruitland - 1271', and Pictured Cliffs - 1326'. Ran 34 jts. (1436.52') 4-1/2", 9.5#, J-55, 8rd, ST&C casing. Bakerloked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1434.12', PBD at 1399.02'. Mixed and pumped 90 sks. (185.4 cu ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk cellophane flakes. Tailed in with 80 sks. (94.4 cu ft) Class "B" cement to surface. Pressure tested casing to 3500 psi for 15 minutes. Waiting on completion.		
14. I hereby certify that the foregoing is true and entrect R R R R R R R R R R R R R	Title Engineering Manager	NOV 0 6 1992
(This space for Federal or State office use)	Time Engineering manager	ACCEPTED FOR APPOARS
	Title	ACCEPTED FOR RECORD
Approved by	Title	Date

NOV 2 0 1997