

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*

(See other instructions on reverse side)

FOR APPROVED  
OMB NO. 1004-0137  
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ OTHER ☐  
b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. ENVR. ☐

2. NAME OF OPERATOR  
Giant Exploration & Production Company

3. ADDRESS AND TELEPHONE NO.

P.O. Box 2810, Farmington, NM 87499 (505) 326-3325

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*

At surface 1850' FSL, 2475' FWL, Sec. 10, T25N, R13W

At top prod. interval reported below

At total depth

14. PERMIT NO. DATE ISSUED

15. DATE STUDDERED 10-26-92 16. DATE T.D. REACHED 10-28-92 17. DATE COMPL. (Ready to prod.) 06-01-93 18. ELEVATIONS (DF, RKB, RT, GE, ETC.)\* 6341' GLE 19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD 1440' 21. PLUG, BACK T.D., MD & TVD 1399' 22. IF MULTIPLE COMPL., HOW MANY\* N/A 23. INTERVALS DRILLED BY → ROTARY TOOLS X CABLE TOOLS

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)\* 1270' - 1285' 25. WAS DIRECTIONAL SURVEY MADE yes

26. TYPE ELECTRIC AND OTHER LOGS RUN Compensated Density-Neutron logs with caliper and gamma ray 27. WAS WELL CORRED no

28. CASING RECORD (Report all strings set in well)				
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD (FT)
7"	20#	130.40'	8-3/4" 60 sy	See Exhibit "A" 714
4-1/2"	9.5#	1434.12'	6-1/4"	See Exhibit "A" 170 sy 279 g.

29. LINER RECORD					30. TUBING RECORD		
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	1286'	

31. PERFORATION RECORD (Interval, size and number)			32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
INTERVAL (MD)	SIZE (IN)	NUMBER	DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
1270' - 1285'	0.40"	60 holes	1270'-1285'	Fraced with 4500# 40/70
				Brady Sand and 12,600#
				12/20 Brady Sand

33.* PRODUCTION							
DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)				WELL STATUS (Producing or shut-in)	
06-01-93		pumping				producing	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
06-01-93	24 hours	1/4"	→	-	3	10	
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	
20	20	→	-	3	10	-	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold TEST WITNESSED BY

35. LIST OF ATTACHMENTS

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records.  
SIGNED Jeffrey R. Vaughan TITLE Vice President of Operations DATE JUN 04 1993

\*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

RY

RECEIVED  
JUN 4 1993  
OIL CON. DIV.  
DIST. 3

RECEIVED  
JUN 7 1993  
FARMINGTON DISTRICT OFFICE

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Fruitland	1074'					
Basal Fruitland	1271'					
Pictured Cliffs	1326'					

38. GEOLOGIC MARKERS

WEST BISTI COAL 10 WELL NO. 2  
1850' FSL, 2475' FWL  
SECTION 10, TOWNSHIP 25 NORTH, RANGE 13 WEST  
LEASE NO. NM - 31311  
SAN JUAN COUNTY  
NEW MEXICO  
COMPLETION REPORT  
EXHIBIT "A"

CEMENT RECORD

Surface Casing - Mixed and pumped 60 sks. (70.8 cu.ft.) of Class "B" cement containing 2%  $\text{CaCl}_2$  and 1/4#/sk. cellophane flakes. Cement circulated to surface.

Production Casing - Mixed and pumped 90 sks. (185.4 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu.ft.) of Class "B" cement containing 2%  $\text{CaCl}_2$  and 1/4#/sk. cellophane flakes. Cement circulated to surface.

185 4  
94  
279 4

80  
90  
170 5x