

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Giant Exploration & Production Company

3. Address and Telephone No.

P.O. Box 2810, Farmington, NM 87499 (505)326-3325

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1850' FNL, 1850' FEL, Sec. 31, T25N, R12W

5. Lease Designation and Serial No.  
NM-36585

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Bisti Coal 31 No. 1

9. API Well No.

10. Field and Pool, or Exploratory Area

Basin Fruitland coal

11. County or Parish, State

San Juan, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Drilling Progress

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled out from under casing with 6-1/4" bit on November 9, 1992. Ran Compensated Density-Neutron logs with caliper and gamma ray. Log tops as follows: Fruitland - 770', Basal Fruitland - 951', and Pictured Cliffs - 1059'. Ran 27 jts. (1162.12') 4-1/2", 9.5#, J-55, 8rd, ST&C casing. Bakerloked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1159.72', PBD at 1115.66'. Mixed and pumped 75 sks. (154.5 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk cellophane flakes. Tailed in with 65 sks. (76.7 cu.ft.) Class "B" cement containing 2% CaCl<sub>2</sub> and 1/4#/sk cellophane flakes. Circulated cement to surface. Pressure tested casing to 3500 psi for 15 min. Waiting on completion.

14. I hereby certify that the foregoing is true and correct

Signed Jeffrey R. Vaughan  
(This space for Federal or State office use)

Title Engineering Manager

Date NOV 24 1992

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_