

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137
Expires: December 31, 1991

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. TYPE OF WELL: OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> DRY <input type="checkbox"/>		JUN 4 1993	
b. TYPE OF COMPLETION: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEP-EN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. REVR. <input type="checkbox"/>		OIL CON. DIV., DIST. 3	
2. NAME OF OPERATOR Giant Exploration & Production Company			
3. ADDRESS AND TELEPHONE NO. P.O. Box 2810, Farmington, NM 87499 (505) 326-3325			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface 1850' FSL, 2310' FWL, Sec. 11, T25N, R13W At top prod. interval reported below At total depth			
14. PERMIT NO.		DATE ISSUED	
15. DATE SPUDDED 12-28-92		16. DATE T.D. REACHED 02-03-93	
17. DATE COMPL. (Ready to prod.) 05-20-93		18. ELEVATIONS (OF, RKB, RT, GR, ETC.)* 6340' GLE	
19. ELEV. CASINGHEAD		20. TOTAL DEPTH, MD & TVD 1400'	
21. PLUG, BACK T.D., MD & TVD 1355'		22. IF MULTIPLE COMPL., HOW MANY* N/A	
23. INTERVALS DRILLED BY →		ROTARY TOOLS X	
24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)* 1230' - 1246'		25. WAS DIRECTIONAL SURVEY MADE yes	
26. TYPE ELECTRIC AND OTHER LOGS RUN Compensated Density-Neutron logs with caliper and gamma ray		27. WAS WELL CORRED no	
28. CASING RECORD (Report all strings set in well)			
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE
7"	20#	127.50'	8-3/4"
4-1/2"	9.5#	1395.28'	6-1/4"
29. LINER RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*
30. TUBING RECORD			
SIZE	DEPTH SET (MD)	PACKER SET (MD)	
2-1/16"	1233'		
31. PERFORATION RECORD (Interval, size and number)			
1230' - 1246' 0.40" 64 holes			
32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.			
DEPTH INTERVAL (MD)		AMOUNT AND KIND OF MATERIAL USED	
1230'-1246'		Fraced with 5,000# 40/70	
		Brady Sand and 31,000#	
		12/20 Brady Sand	
33.* PRODUCTION			
DATE FIRST PRODUCTION 05-20-93		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) flowing	
WELL STATUS (Producing or shut-in) producing			
DATE OF TEST 05-20-93	HOURS TESTED 24 hours	CHOKE SIZE 1/2"	PROD'N. FOR TEST PERIOD →
OIL—BBL. 0	GAS—MCF. 98	WATER—BBL. 2	GAS-OIL RATIO
FLOW. TUBING PRESS. 1 psi	CASING PRESSURE 80	CALCULATED 24-HOUR RATE →	OIL GRAVITY-API (CORR.)
OIL—BBL. 98	GAS—MCF. 2	WATER—BBL.	
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold			
35. LIST OF ATTACHMENTS			

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

John C. Corbett

TITLE

Senior Vice President

DATE JUN 01 1993

JUN 02 1993

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make (to any agency of the United States) any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

NMCCD

ACCEPTED FOR RECORD
FARMINGTON DISTRICT OFFICE
BY

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, flowing and shut-in pressures, and recoveries):

38. GEOLOGIC MARKERS

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
Fruitland	1056'					
Basal Fruitland	1230'					
Pictured Cliffs	1282'					

WEST BISTI COAL 11 WELL NO. 2
1850' FSL, 2310' FWL
SECTION 11, TOWNSHIP 25 NORTH, RANGE 13 WEST
LEASE NO. NM - 31311
SAN JUAN COUNTY
NEW MEXICO
COMPLETION REPORT
EXHIBIT "A"

CEMENT RECORD

- Surface Casing - Mixed and pumped 60 sks. (70.8 cu.ft.) of Class "B" cement containing 2% CaCl_2 and 1/4#/sk. cellophane flakes. Cement circulated to surface.
- Production Casing - Mixed and pumped 100 sks. (206.0 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk. cellophane flakes. Tailed in with 80 sks. (94.4 cu.ft.) of Class "B" cement containing 2% CaCl_2 and 1/4#/sk. cellophane flakes. Cement circulated to surface.