

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM - 69534 87236

6. If Indian, Allottee or Tribe Name

Navajo Tribe

7. If Unit or CA, Agreement Designation

8. Well Name and No.

West Bisti Coal 14 Com #1

9. API Well No.

30-045-28914

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan, New Mexico

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Giant Exploration & Production Company

3. Address and Telephone No.

P.O. Box 2810, Farmington, N.M. 87499 (505) 326-3325

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

790' FNL, 790' FEL, Sec. 14, T25N, R13W, NMPM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Drilling Progress

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled out from under casing with 6-1/4" bit on January 25, 1993. Ran Compensated Density-Neutron logs with caliper and gamma ray. Log tops as follows: Fruitland - 1097', Basal Fruitland - 1294' and Pictured Cliffs - 1348'. Ran 36 jts. (1544.83') 4-1/2", 9.5#, J-55, 8rd, ST&C casing. Bakerloded cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1544.93', PBD at 1508.33'. Mixed and pumped 100 sks. (206 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk cellophane flakes. Tailed in with 90 sks. (106.2 cu.ft.) Class "B" cement containing 2% CaCl₂ and 1/4#/sk cellophane flakes. Circulated cement to surface. Pressure tested casing to 3500 psi for 15 minutes. Waiting on completion.

RECEIVED

FEB 25 1993

OIL CON. DIV.

DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Jeffrey R. Vaughan

Title Engineering Manager

Date

FEB 12 1993

Approved by
Conditions of approval, if any:

Title

ACCEPTED FOR RECORD

Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOC

FARMINGTON FIELD OFFICE