Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FOF IVEU

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

Change of Plans

Dispose Water

New Construction

☐ Non-Routine Fracturing
☐ Water Shut-Off

Conversion to Injection

BUKLAU	OF THE MANAGEMENTS PER A CO	
	DIMMAII ROU	5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS		NM-57453
Do not use this form for proposals to drill or to deepen or reentry to a different py 2: reservoir.		Aff Indian, Allottee or Tribe Name
Use "APPLICATION FOR PERMIT" for such proposals 070 FARMINGTON,		NM
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
1. Type of Well		8. Well Name and No.
Oil Gas		
☐ Well    Well  ☐ Other		LY FEDERAL #1
2. Name of Operator MYCO INDUSTRIES, INC.		9. API Well No. 30-045-29113
3.Address and Telephone No.		10. Field and Pool, or Exploratory Area
P O BOX 840, ARTESIA, NM 88210		BASIN-FRUITLAND COAL
4. Location of Well (Footage, Sec., T., R., M., or Survey Description		11. County or Parish, State
2490' FSL & 1780' FWL S34-T25N-F31W 1300		SAN JUAN CO., NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION	

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

SPUDDED 6/14/94

Notice of Intent

Subsequent Report

Final Abandonment Notice

RAN 4-JTS 23# J55 CASING TO 135', CEMENT WITH 60-SXS CLASS B 1/4# CELLO FLAKE 2% CaCl CIRCULATE 20-SXS TO PIT, PLUG DOWN @ 2 PM 6/14/94.

Other RAN CASING

Abandonment

Recompletion

Plugging Back

Casing Repair

Altering Casing

NOTIFY MARKO KOCHMANWITL OF THE BLM ON 6/17/94 AT 8:25 AM.

RAN 28-JTS 4-1/2" 10.5# J-55 ST&C CASING TO 1200', CEMENT 4-1/2" CASING WITH

200-SXS CLASS B 1/4# FLOCELE 2% CaCl PLUG DOWN @ 1:45 PM 6/17/94. CIRCULATE

12-SXS TO THE PIT. PBTD=1156'. RAN GUIDE SHOE 1-JT 4-1/2" CASING 43.50' FLOAT

COLLAR 27-JTS 4-1/2" CASING. CENTRALIZERS ON JTS# 1,3,5,7,9. RELASE RIG @ 2PM, 6/17/94.

PREP TO COMPLETE WELL. WELL CASED HOLE LOGS TO FOLLOW.

OH COM. DIV.

JUN 3 0 1994

\*See Instruction on Reverse Side