Form 3160-5 (June 1990)

RECEIVED BLM

FF 18 PM 3: 25

FORM APPROVED
Budget Bureau No. 1004-0135

Expires: March 31, 1993

5. Lease Designation and Serial No. SF 078063

6. If Indian, Allottee or Tribe Name

BUREAU OF LAND MANAGEMENT 18 P SUNDRY NOTICES AND REPORTS ON WELLS

UNITED STATES

DEPARTMENT OF THE INTERIOR

Do not use this form for proposals to drill or to deepen or reently to a different reservoir.

Use "APPLICATION FOR PERMIT--" for such proposals

7. If Unit or CA. Agreement Designation

000 122 251011110		i	
SUBMIT IN TRIPLICATE		Carson Unit	
1. Type of Well X Oil Well Ga	as Well Other	8. Well Name and No. Farfelu #1	
2. Name of Operator		9. API Well No.	
Central Resources, Inc. for	NA 30-045-29426		
3. Address and Telephone No.		10. Field and Pool, or Exploratory Area	
P.O. Box 2810, Farmington	Basin Dakota		
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State	
1650' FSL, 880' FEL, Sec. 19, T25N, R11W		San Juan, New Mexico	
12. CHECK APPROPRIATE BOX	(s) TO INDICATE NATURE OF NOTICE, REPO	RT, OR OTHER DATA	
TYPE OF SUBMISSION	TYPE OF ACT	ION	
	Abandonment	X Change of Plans	
X Notice of Intent	Recompletion	New Construction	
	X Plugging Back	Non-Routine Fracturing	
Subsequent Report	Casing Repair	Water Shut-Off	
_	Altering Casing	Conversion to Injection	
Final Abandonment Notice	Other Temp. Abandonment	Dispose Water	
		(Note: Report results of multiple completion on Well	
		Completion or Recompletion Report and Log form.)	
13. Describe Proposed or Completed Operations (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*			

Central Resources, Inc. plans plug back and alter the casing and cement program on the subject well as follows: Set a Class B cement (1.18 yield, 15.6 ppg) plug from 7025' to 6800', as verbally approved by Wayne Townsend. Set 5-1/2", 15.5#, J-55 casing at 6000'. Centralizers every 40' from 6000' to 5600' and 5000' to 4600',

total of 20 centralizers.

Cement with 510 sacks Class B cement mixed with 3% Econolite and 5#/sk Gilsonite (2.85 yield, 11.4 ppg). Tail in with 375 sacks 50/50 poz cement with 1/4#/sk cellophane, 5# Gilsonite and 0.4% Fluid loss (1.25 yield, 13.5 ppg). Displace and bump plug.

14. I hereby, certify that the foregoing is true and correct		
Signed July 7 Matel	Title Production Engineer	Date12/18/96
Gregory E. McIntosh		7
(This space for Federal or State office use)		ROVED
Approved by	Title	Date
Conditions of approval, if any:		DEC 2 3 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United Statisticious or fraudulent statements or representations as to any manner within its jurisdiction.