Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

5. Lease Designation and Serial No.

NOO-C-14-20-3618

SHNDRY NOTICES	AND REPORTS ON WELLS	N00-C-14-20-3016
		6. If Indian, Allottee or Tribe Name
	ill or to deepen or reentry to a different reservoir. R PERMIT—" for such proposals	Navajo Nation Allottee
SUBMIT	IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well		CA-SWI-4298
Oil X Gas Other	DEGETAL DOOR	8. Well Name and No.
2. Name of Operator	( )	Canyon #7E
Cross Timbers Operating Comp	any III NOV 3	9. API Well No.
3. Address and Telephone No.	- GOMO DU	<sup>y</sup> 30-045-29710
6001 Highway 64, Farmington,	111111111111111111111111111111111111111	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey D	escription)	Basin Dakota
	a a	11. County or Parish, State
1500' FNL & 1500' FEL, Sec.	15, T25N, R11W, Unit Ltr G	San Juan Co., NM
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
X Subsequent Report	Plugging Back	Non-Routine Fracturing
	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
*	X Other Spud & Surface Casing	Dispose Water
		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state al	pertinent details, and give pertinent dates, including estimated date of starting a	any proposed work. If well is directionally drilled,
give subsurface locations and measured and true vertice	al depths for all markers and zones pertinent to this work.)*	

MI & RU rotary. Spudded 12-1/4" hole @ 11:30 p.m. (MST), 11/08/98. Drilled to 337' and ran 8-5/8", 24#, J-55, STC casing and set @ 331'. Rigged up BJ Services and cemented casing w/225 sx C1 H cement w/2% CaC1 and 1/4#/sx Celloflake. Displaced w/19 bbls fresh water. Plug down @ 10:45 a.m., 11/09/98, w/100 psig. Did not bump plug. Float held OK. Circulated 30 sx cement to surface. WOC 4 hrs. NU BOP and tested to 1000 psig, held OK. Prep to drill out cement w/7-7/8" bit.

## ACCEPTED FOR HELOHI

NOV 24 1998

FARMINGTON DISTRICT OFFICE

. I hereby certify that the foregoing is true and correct Signed Bobby Smath	Title Drilling/Operations Manager	Date 11/10/98
(This space for Federal or State office use) Bobby L. Smit	th	
Approved by	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.