

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

RECEIVED  
APR 27 1999  
OIL CON. DIV.  
DIST. 3

5. Lease Designation and Serial No.

NO-G-9403-1260

6. If Indian, Allottee or Tribe Name

Navajo Allotted

7. If Unit or CA, Agreement Designation

CA Pending

8. Well Name and No.

Gracia Navajo 22 # 1

9. API Well No.

30-045-29797

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County, NM

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Pro NM Energy, Inc. (OGRID 018118)

3. Address and Telephone No.

460 St. Michael's Dr., # 402, Santa Fe, NM 87505 505/988-4171

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1135' FSL; 1805' FWL  
Section 22-T25N-R11W

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Set Surface Casing  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Ran 4 joints 8-5/8" 24 # K-55 STC surface casing, 177.60'. Set top casing collar 2' below ground level. Land casing at 183.60' KB. Pump 5 BBL water followed by 150 sx (177 cubic feet) of Class B cement with 3% CAC12 and 1/4# 1sx cellophane flakes mixed at 15.6 ppg. Displace with 7.5 BBL water. Circulated 5 BBLs good cement to surface. Shut in casing with 100#.

RECEIVED  
BLM  
APR 21 PM 12:28  
070 FARMINGTON, NM

cc: NMOCD

14. I hereby certify that the foregoing is true and correct

Signed Curtis J. Shaw

Title Production Technician / Agent

Date 04/15/99

(This space for Federal or State office use)

Approved by \_\_\_\_\_  
Conditions of approval, if any:

Title \_\_\_\_\_

Date \_\_\_\_\_

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

\*See Instruction on Reverse Side  
NMOCD