

CEMENT JOB REPORT

CUSTOMER Maralex Resources Inc			DATE 12-APR-00		F.R. # 216417664			SERV. SUPV. Richard H Kovacs				
LEASE & WELL NAME Carson Trading Post 25 #2			LOCATION Sec25-T25N-R11W					COUNTY-PARISH-BLOCK San Juan New Mexico				
DISTRICT Farmington			DRILLING CONTRACTOR RIG # L&B Speed Drill				TYPE OF JOB Surface					
SIZE & TYPE OF PLUGS		LIST-CSG-HARDWARE			PHYSICAL SLURRY PROPERTIES							
Cement Plug, Rubber, Top 8-5/8 in		Float Shoe 8-5/8 - 8rd			SLURRY WGT PPG	SLURRY YLD FT ³	WATER GPS	PUMP TIME HR:MIN	Bbl SLURRY	Bbl MIX WATER		
MATERIALS FURNISHED BY SJ												
Fresh Water					8.34				10			
Type III + Add.					14.6	1.40	6.68		24.92	15.91		
Fresh Water					8.34				7.64			
Available Mix Water 20 Bbl.					Available Displ. Fluid 54 Bbl.		TOTAL		42.56	15.91		
HOLE			TBG-CSG-D.P.					COLLAR DEPTHS				
SIZE	% EXCESS	DEPTH	SIZE	WGT.	TYPE	DEPTH	GRADE	SHOE	FLOAT	STAGE		
12.25		140	8.625	24	CSG	140		134.7	94.7			
LAST CASING			PKR-CMT RET-BR PL-LINER			PERF. DEPTH		TOP CONN		WELL FLUID		
SIZE	WGT	TYPE	DEPTH	BRAND & TYPE		DEPTH	TOP	BTM	SIZE	THREAD	TYPE	WGT.
									8.625	8RND	WATER BASED MUD	9
DISPL. VOLUME			DISPL. FLUID		CAL. PSI	CAL. MAX PSI	OP. MAX	MAX TBG PSI		MAX CSG PSI		MIX WATER SOURCE
VOLUME	UOM	TYPE	WGT.	BUMP PLUG	TO REV.	SQ. PSI	RATED	Operator	RATED	Operator		
7.6	BEELS	Fresh Water	8.34	33	0	0	0	0	2950	2360	Water Truck	

EXPLANATION: TROUBLE SETTING TOOL, RUNNING CSG, ETC. PRIOR TO CEMENTING:

PRESSURE/RATE DETAIL						EXPLANATION	
TIME HR:MIN.	PRESSURE - PSI		RATE BPM	Bbl. FLUID PUMPED	FLUID TYPE	SAFETY MEETING: BJ CREW ☒ CO. REP. ☒	
	PIPE	ANNULUS				TEST LINES	1000 PSI
						CIRCULATING WELL - RIG ☒ BJ ☐	
11:42	1000		1		H2O	ST PRESSURE TEST 1000PSI	
11:43	30		3	1	H2O	ST 10BBLS AHEAD	
11:47	3		3	10	CMT	ST CEMENT 258BLS @14.5	
11:54	9		3	25	H2O	ST DISPLACMENT 68BLS	
11:56	7		0	60		SHUT DOWN SHUT IN	
BUMPED PLUG	PSI TO BUMP PLUG	TEST FLOAT EQUIP.	BBL.CMT RETURNS/ REVERSED	TOTAL BBL. PUMPED	PSI LEFT ON CSG	SPOT TOP OUT CEMENT	SERV. SUPV.
Y ☒ N	0	Y ☒ N	7	41	7	☒ Y ☐ N	