


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. SP-076048  
Unit \_\_\_\_\_



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING <input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 24, 19 57

Well No. 5-30 Hughes is located 1850 ft. from [N] line and 1850 ft. from [W] line of sec. 30  
SE/4, Section 30 T-26-N, R-7-W N.M.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Ballard Pictured Cliffs Rio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6314 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

T.D. 2300'. PWD 2220'. Perforated Pictured Cliffs formation 2165-92 with 4 shots per foot. Fraced with 1240 barrels water 50,000 lbs. sand, flushed with 160 barrels water. Breakdown Pressure 2975 lbs., Trapping Pressure 1500 lbs., Final Pressure 775 lbs., Injection Rate 60 gpm.

Landed 2207' of 1" tubing at 2216'. S.I.G. 9-7-57.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company WOFFORD CAIN

Address P O Box 706

Farmington, New Mexico

By Joe C. Salmon  
Joe C. Salmon  
Title Representative for Wofford Cain