

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐
2. NAME OF OPERATOR  
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR  
P. O. Box 289, Farmington, N. M. 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1650'S, 1650'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED  
OCT 20 1981  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF 079034
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
Scott
8. FARM OR LEASE NAME  
SCOTT A
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
S. Blanco  
Dogto Canyon P.C.
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 24, T26N, R7W
12. COUNTY OR PARISH  
Rio Arriba
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6520' D.F.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/19, 20-81

1. Pull 2684' of 1" tubing, run 2700' of 1 1/4" tubing in hole and circulate.
2. Spot .8 sx cement plug in hole 2705'-2582'.
3. Spot cement plug from 2357' to 2257'.
4. Perforate w/2 shots at 1700'. Circulate, squeeze w/60 sx. cement through perforations.
5. Leave annulus between surface and production casing full of cement and cement plug inside production casing.
6. Spot .0 sx. cement plug.
7. Install P & A marker.

Perforated at 180' and circulated 75 sx cement plug from 180' to 40'

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED \_\_\_\_\_ TITLE Production Engineer DATE 10-21-81

(This space for Federal or State office use)

APPROVED BY JR Bourne TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

"Complied with general requirements. Site ready for inspection."

NMOCC

\*See Instructions on Reverse Side