

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	5. LEASE DESIGNATION AND SERIAL NO. NM 011639
2. NAME OF OPERATOR E. L. Fundingsland	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 7400 East Orchard Road, Suite #240, Englewood, CO. 80111	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 980' FWL	8. FARM OR LEASE NAME Sunical # Food
	9. WELL NO. 4
	10. FIELD AND POOL, OR WILDCAT Basin Dakota
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 20 - 26N - 7W
14. PERMIT NO. Dec. 13, 1985	12. COUNTY OR PARISH Rio Arriba
15. ELEVATIONS (Show whether by RT, GN, etc.) 6252 KB	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other)

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other)

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

5-31-86 Installed BOP, pulled tubing. Tubing used to spot all plugs.

6-2-86 Spotted 100 sxs. Class B cement from 6740' to 5400'. Loaded hole with 9.2 mud. Perf 1 hole @ 3802'. Squeezed perf. with 30 sxs. Class B cement. Top of cement @ 3695'. Perf. 1 hole @ 3100'. Squeezed perf. with 25 sxs. Class B cement. Top of cement @ 2995'. Spotted 35 sxs. Class B cement from 2236' to 1823'. Perf. 1 hole @ 1475'.

6-3-86 Squeezed perf. with 25 sxs. Class B cement. Top of cement @ 1365'. Spotted 25 sxs. Class B cement from 314' to surface. Squeezed bradenhead with 25 sxs. Class B cement. Removed well head. Cut off 8 5/8" surface pipe and 4 1/2" casing. Weld plate and install dry hole marker.

Surface restoration and reseedling will be completed by September 30, 1986

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

18. I hereby certify that the foregoing is true and correct

SIGNED E. L. Fundingsland TITLE Vice President

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

*See Instructions on Reverse Side

NMOCC

