
	9-8818
⊄F eb	. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES **DEPARTMENT OF THE INTERIOR** GEOLOGICAL SURVEY

Land Office	Canta	Fe
Lease No	079360)
Unit	Rinco	1

	ICES AND REPORTS ON WELLS
NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF.
NOTICE OF INTENTION TO CHANGE PLANS	The second of th
NOTICE OF INTENTION TO TEST WATER SHUT-OI	FFSUBSEQUENT REPORT OF ALTERING CASING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR	WELL SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT.
NOTICE OF INTENTION TO PULL OR ALTER CASH	NGSUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Water Fracture
(INDICATE ABOVE B	Y CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	September 7, 19
	5 ft. from [N] line and 920 ft. from E line of sec. 22
RE Section 22 27N (4 Sec. and Sec. No.)	vp.) (Range) (Meridian)
Sc. Blanco P.C.	(Mendial)
(Field)	Rio Arribe New Mexico (County or Subdivision) (State or Territory)
tate names of and expected depths to objective as ing po 9-4-56 Total Depth 3165'. (Water fractured Pictured C)	Iffe perforeted intermed 2015 to each by one was
9-4-56 Total Depth 3165'. (Water fractured Pictured Cli	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cem sints, and all other important proposed work) 2.0. to 3131. Iffs perforated interval 3015-50 with 41,200 gall sakdown pressure 2850#, maximum pressure 2850#, Flush 3500 Flush 3500
tate names of and expected depths to objective so ing po 9-4-56 Total Depth 3165'. (Water fractured Pictured Cli water and 40,000f sand. Bre average treating pressure 18 gallons.	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cempints, and all other important proposed work) C.O. to 3131'. Liffs perforated interval 3015-50 with 41,200 gall sakdown pressure 2850#, maximum pressure 2850#, 300\$. Injection rate to Control of Con
tate names of and expected depths to objective as ing possible. 9-4-56 Total Depth 3165'. (Water fractured Pictured Cliwater and 40,000% sand. Breaverage treating pressure 18 gallons. I understand that this plan of work must receive the pressure ompany. El Paso Natural Galdress. Box 997	ands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cempany, and all other important proposed work) C.O. to 3131'. Liffs perforated interval 3015-50 with 41,200 gall sekdown pressure 2850#, maximum rressure 2850#, 2007. Injection rate 60 performance of the company of the Geological Survey before operations may be commenced.



