

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency _____

Jicarilla Tribal

Allottee _____

Lease No. Jicarilla Tribal 297

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Jicarilla Tribal 297

Farmington, New Mexico January 20, 1961

Well No. 1 is located 471.9 ft. from S line and 1295 ft. from E line of sec. 29
Lot 4 Section 29 T-27-N R-1-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Puerto Chiquito Gallup Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7058 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

As a result of not obtaining oil or gas in commercial quantities, Jicarilla Tribal 297 Well No. 1 was plugged and abandoned as follows on January 6, 1961:

1. Moved in pulling unit.
2. Ran Baker cast iron retainer on the tubing and set at 1765'. Squashed with 100 sack cement plug 1765-1798.
3. Pulled tubing and ran fire point. Casing stuck at 1750, moderately loose at 1700, and free at 1650'. Out off casing at 1640' and recovered 1640' 5-1/2" casing.
4. Ran 2" tubing and hit bridge at 1430'. Filled hole with mud and ran Baker Model K No. 7 cast iron open hole bridge plug set at 553'. Pumped 2 sacks cement containing 2% calcium chloride on top of plug.
5. Ran tubing to 527' and spotted 135 sacks cement containing 2% calcium chloride. Top cement at 320'.
6. Spotted 10 sack cement plug at surface and erected abandonment marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Pan American Petroleum Corporation

Address Box 440

Farmington, N. M.

Attn: L. O. Speer, Jr.

ORIGINAL SIGNED BY

R. M. Bauer, Jr.

By _____

Title Senior Petroleum Engineer