30-039-06772

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator B	URLINGTON RESOURCE	ES OIL & GAS CO.	1	Lease	SAN JUAN 27-4	UNIT NP		Well No.	30	
Location		_		_		_				
of Well:	Unit N Sect	32 Twp.		Rge.	7PE OF PROD.	County	RIO ARRIBA OD OF PROD.		D MEDITA	
	NAME OF RESERVOIR OR POOL				(Oil or Gas)		(Flow or Art. Lift)		PROD. MEDIUM (Tbg. or Csg.)	
Upper Completion	GALLUP			Gas		Flow			Casing	
Lower Completion	DAKOTA				Gas		Flow		Tubing	
		PRE-I	FLOW SHUT-IN I	PRESS	URE DATA					
Upper	Hour, date shut-in Length of time shut-in			SI press. psig Stab			Stabilized? (Y	bilized? (Yes or No)		
Completion	4/17/98	120 Ho	ours		11					
Lower Completion	4/17/98	72 Ho	urs		742					
			FLOW TEST	ΓNO.	_					
	d at (hour,date)* 4/20/98			Zone producing (Upper of			ower) LC	WER	-, ·	
TIME	LAPSED TIME				PROD. ZONE					
(hour,date)	SINCE*	Upper Completion	Lower Complet	ion	ТЕМР		REMARKS			
4/21/98	96 Hours	1	570	GALLUP NO			JP NOT PRDU	ICING D	ISCONECTED	
4/22/98	120 Hours	1 499								
						50				
					n n	JUH	1 9 880			
D 1					@[
Production rate	e during test					D	\$16 D		**	
Oil:	BOPD based on	Bbls. i	in	Hours	•	Grav		_ GOR		
Gas:		MCFPD; Tested thru ((Orifice or Meter):					·	·	
		MID	-TEST SHUT-IN I	PRESS	URE DATA					
Upper Completion	Hour, date shut-in	Length of time shut-in		SI press. psig		Stabilized? (Yes or No)				
Lower Completion	Hour, date shut-in	Length of time shut-in		SI press. psig		Stabilized? (Yes or No)				

(Continue on reverse side)

FLOW TEST NO. 2 Zone producing (Upper or Lower): Commenced at (hour, date) ** PRESSURE PROD. ZONE LAPSED TIME TIME REMARKS SINCE ## Lower Completion TEMP. (hour, date) **Upper Completion** Production rate during test Oil: BOPD based on Bbls. in Hours. Grav. GOR MCFPD: Tested thru (Otifice or Meter): ____ Gas: ____ Remarks: I hereby certify that the information herein contained is true and complete to the best of my knowledge.

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken as any time that communication is suspected or when requested by the Division.

Johnny Rolincon

New Mexico Oil Conservation Division

Approved _____

Title _

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Procedure for Flow Ten No. 2 is to be the same as for Flow Ten No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previous ly shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at lifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each

flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least rwice, once at the beginning and once at the end of each test, with a desdweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing , temperatures (gas zones only) and gravity and GOR (oil zones only).