



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. 07239

Unit Sun Juan 27-5 Unit
14-08-601-730

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	<u>Water Free.</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 14, 1960

Well No. 56 (TM) is located 1650 ft. from S line and 990 ft. from W line of sec.

S. W. 1/4 Sec. 34 27 N 3 W A.M.P.M.
(Sec. and Sec. No.) (Twp.) (Range) (Meridian)

So. Blanco P.C. (Ext.) Blanco N.V. Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6539 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

7-11-60 Total Depth. C.O.T.D. 5571. Water free. Point Lockout perforated intervals 5256-74; 5486-36; 5488-90; 5496-5500; 5508-5510; 5528-30; 5536-40; 5544-50 with 36,750 gal. water and 50,000 # sand. Breakdown pr. 3000 #, max. pr. 3000 #, avg. tr. pr. 2500 #. I.R. 50 B.P.M. Flush 9,840 gallons.
7-11-60 Total Depth 5624. Bangor B.P. at 5100. Water free. Cliff House perf int. 4874-76; 4886-90; 4964-68; 4996-5004; with 25,820 gal. water and 25,000 # sand. Breakdown pr. 3000 #, max. pr. 3000 #, avg. tr. pr. 1800-2100 #. I.R. 69.6 B.P.M. Flush 8,400 gallons. Drugged 1 set of 10 balls. Spotted 250 gal. B.D.A. across perfor to break down.
7-12-60 Total Depth 5624. Tum. B.P. at 4500. Water free. Pictured Cliffs perf int. 3838-46; 3876-86; 3896-3912 with 32,840 gallons water and 3200 # sand. Break down pr. 1900 #, max. pr. 3000 #, avg. tr. pr. 1700-2150 #. I.R. 67.0 B.P.M. Flush 7,980 gal. Drugged 1 set of 15 balls.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990

Farmington, New Mexico

ORIGINAL SIGNED H.E. McANALLY

By _____

Title Petroleum Engineer