STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

										Well	
Operator B	BURLINGTON RESOURCES OIL & GAS CO.					Lease	SAN JUAN 27-	5 UNIT		No. 8	
ocation											
of Well:	Unit	L	Sect	32 Twp.	027N	Rge.	005W	County	RIO ARRIBA		
			NAME OF	RESERVOIR OR POO	L	T	PE OF PROD.	METH	OD OF PROD.	PRO	OD. MEDIUM
					. <u>-</u>		(Oil or Gas)	(Flov	v or Art. Lift)	0	Tbg. or Csg.)
Upper Completion	PICTURED CLIFFS						Gas	Flow			Tubing
Lower Completion	MES	AVER	DE				Gas	Flow			Tubing
				PRE-	FLOW SHUT-IN	PRESS	URE DATA				
Upper	Hour, date shut-in			Length of time shut-	SI press. psig Stabil		Stabilized? (Ye	ized? (Yes or No)			
Completion	4/19/98		/98	120 Hours		0					
Lower Completion	4/19/98			72 Hours			432				
					FLOW TE	ST NO.	l				
Commenced	at (hour,	date)*		4/22/98			Zone producing	(Upper or L	ower) LO	WER	
TIME	LAPSED TIME			PRESSURE			PROD. ZONE			-	
(hour,date)	SINCE*		CE*	Upper Completion Lower Comp		etion	ТЕМР	REMARKS			
4/23/98	96 Hours		ours	0	323			opene	opened lower zone for flow		
4/24/98	120 Hours			0 224					300		
									TEC!		
			_						JUN 1	<u>°: 1,9</u> .Gac	
									IL Con	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
						-	<u> </u>	DIE		The state of the s	
roduction rate	during t	est	•	<u> </u>				:1		· · ·	
S11.		DODE	\ \ d	Bbls, i	<u></u>	Uauaa		Grav.		COR	
Dil:		BULL) based on _	Dois. 1	<u> </u>	Hours.		Grav.		GOR	
Gas:				MCFPD; Tested thru (Orifice or Meter)	:					
					THOT OLD TO S						
	11	4-4-			-TEST SHUT-IN			· · · · · · · · · · · · · · · · · · ·	G4-E11 10 C1		
Upper Completion	Hour	, date sh	iut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No)		
Lower Completion	Hour,	, date sh	ut-in	Length of time shut-	in	SI pr	ess. psig		Stabilized? (Yo	es or No)	

(Continue on reverse side)

FLOW TEST NO. 2

-2.				Cone presucing (Upp			
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	REMARKS		
(hour, dete)	SINCE **	Upper Completion	Lower Completion	TEMP.			
	- 	ļ					
	·	 					
			1				
	 						
					Grav		
						,,	
narks: ereby certify to proved New Mexico C	that the informat	ion herein contain 1998 Division	ned is true and co	Detator SM	I of my knowledge Lington Se W Hay Hom and	www.	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Ten No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced sone shall remain shut-in while the zone which was previously shut-in as produced.
- 7. Pressures for gas-none term must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-posted, at fifteen-monute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day term: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 13 days after completion of the test. Tests shall be filed with the Astec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).