

COPY FOR
STATE OF NEW MEXICO
OIL CONSERVATION
COMMISSION
SUBMIT IN TRIPLICATE TO
DISTRICT OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office _____

Lease No. ST 080511

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	<u>Report on Plugging</u>	<u>I</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. Har. 4 is located 2240 ft. from N line and 2250 ft. from E line of sec. 31

NE 1/4 31 (1/4 Sec. and Sec. No.) 27 (Twp.) 7 (Range) N. M. (Meridian)
Wildest (Field) Rio Arriba (County or Subdivision) N. M. (State or Territory)

The elevation of the derrick floor above sea level is 6046 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddling jobs, cementing points, and all other important proposed work)

Ran a concrete plug to 1600'. Perforated (done by Lane Wells) with 4 shots at 1574'. Picked up circulation. Pumped 80 sacks cement. Left 20' of cement in the pipe above 1574'. Work done by Halliburton. Cement squeeze job with 80 sacks at 1574'.

When cement dries, will perforate from 1530' to 1490' and 1440' to 1400' and test.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company N. J. Florence
Address Alto, N. M.

By Joyce E. Lushenberger
Title Geologist

