

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. SF-080385
2. NAME OF OPERATOR Union Oil Company of California dba Unocal		6. IF INDIAN, ALLOTTEE OR TRIBE NAME NA
3. ADDRESS OF OPERATOR P.O. Box 850 Bloomfield, New Mexico 87413		7. UNIT AGREEMENT NAME Rincon Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below) At surface Rincon 76 - 1800'FNL & 1090'FEL Rincon 124 - 1800'FNL & 815'FEL		8. FARM OR LEASE NAME Rincon
14. PERMIT NO.		9. WELL NO. 76, 124
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 76-6694'DF 124-6702'DF		10. FIELD AND POOL, OR WILDCAT Pictured Cliff, Mesa Verde
		11. SEC., T., R., M., OR S.W. AND SURVEY OR AREA Sec. 34 T27N R7W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐ ABANDON* ☐
REPAIR WELL ☐ CHANGE PLANS ☐
(Other) Install Cathodic Protection

WATER SHUT-OFF ☐ REPAIRING WELL ☐
FRACTURE TREATMENT ☐ ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐ ABANDONMENT* ☐
(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED WORK. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.

Proposed installation of cathodic protection to well casing:

Procedure: Drill a 6" diameter hole, 300 ft. deep within the existing well location boundary. Six Lida ST-1.60/50 anodes will be installed below the uppermost waterbearing formation, and back filled with coke breeze (99.5% carbon) to completely surround the anodes. Backfill rest of hole with gravel or drilling tailings.

A DC rectifier will be installed on the existing well location and a buried DC positive cable will be connected to the Lida ground bed from the rectifier. Negative DC cables from the rectifier will also be buried and connected to the well casings to be protected. These cables will be buried 18" to 24" deep in the middle of the road as shown on attached map. Therefore, an archaeological study will not be submitted because all work will take place on previously disturbed ground.

Unocal's completion expectation is by July 15, 1990.

RECEIVED

JUN 26 1990

OIL CON. DIV.
DIST. 3

ACCEPTED FOR RECORD
EVALUATION

18. I hereby certify that the foregoing is true and correct

SIGNED

Mike Jabet

TITLE Production Technician

DATE

03/05/1990

Ken Townsend

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMOCD

*See Instructions on Reverse Side