



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-R359.4.

Indian Agency Palo Alto

Allottee Alamogordo Tribal

Lease No. Contract 237

SUNDRY NOTICES AND REPORTS ON WELLS

RECEIVED
JUL 15 1963

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Management Report of Sand-411
	Fracture Treatment

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 11, 1963

Well No. 7-19 is located 660 ft. from [N] line and 660 ft. from [E] line of sec. 19
SE/4 12/4 Sec. 19 27N 1E N.M.P.M.
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Paria, Chiquito Rio Arriba New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7050 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

6-1-63 Pumped in 250 gallons 15% bromine acid followed with 100 barrels oil. Perforated 3012-3015 with 1 shot per foot, at 2940' with 1 shot, from 2933' to 2950 with 1 shot per 2', from 2936' to 2940' with 1 shot per 2', from 2905' to 2920' with 1 shot per 2', from 2895' to 2905' with 1 shot per 2', from 2895' to 2905' with 1 shot per foot. Sand-oil treated with 51,000 gallons oil and 50,000 lb. sand, followed with 10,000 lb. sand, flushed with 1,500 gallons oil. Average injection rate 45 barrels per minute. No apparent breakdown pressure. Average treating pressure 2900'. Instantaneous shut-in pressure 2900', 10-minute shut-in pressure 2890'. Run tubing to pump lead oil.

I understand that this plan of work must receive approval in writing by the Geological Survey before operating.

Company INDEPENDENT-AMERICA-CHINA DRILLING CORP.

Address 158 Petroleum Center Building

Alamogordo, New Mexico

By Albert S. Siler

Title Vice-President



