

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe

Lease No. NM 03547

Unit _____

Derrick "J"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 14, 1959

Well No. PND-8 is located 990 ft. from N line and 990 ft. from E line of sec. 34


NE 1/4 (1/4 Sec. and Sec. No.) 27N (Twp.) 6W (Range) NM 21 (Meridian)
South Platte (Field) Rio Arriba (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6616 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to TD - 4662' 3-11-59
Ran 7 5/8", 2640', J-55 Brd Casing to 4662'. Guide Shoe at 4662'.
Float Collar at 4642', DV Tool at 3300' and Centralizers at 4607',
4512', 4420, 3333', 3266', 3233', 3202, and 3171'.
Cemented first stage w/225 sacks regular cement.
Plug down 2:30 PM, 3-11-59.
Cemented 2nd stage through DV Tool set at 3300' with 130 sacks
Pozmix followed by 50 sacks neat.
Plug down 4:45 PM, 3-11-59.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Caulkins Oil Co.

Address P. O. Box 967

Farmington, New Mexico

By Frank Gray

Title Field Superintendent