TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING MULTIPLE COMPLETE

CHANGE ZONES

Form Approved

SUNDRY	NOTICES	AND	REPORTS	ON	WELLS			
	DEPARTMEN	NT OF	THE INTERI	OR				
c. 1973	UNITED STATES							

Dec. 1973	Budget Bureau No. 42-R1424				
UNITED STATES	5. LEASE				
DEPARTMENT OF THE INTERIOR	NM 03547				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME				
reservoir. Use form 9–331–C for such proposals.)	8. FARM OR LEASE NAME				
1. oil _ gas _	Breech "F"				
well well well other	9. WELL NO.				
2. NAME OF OPERATOR	12				
Caulkins Oil Company	10. FIELD OR WILDCAT NAME Blanco Mesa Verde				
3. ADDRESS OF OPERATOR	South Blanco Pictured Cliffs				
P.O. Box 780 Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17					
below.)	Section 35, 27 North, 6 West				
AT SURFACE: 990' From North & 990' From East	12. COUNTY OR PARISH 13. STATE				
AT TOP PROD. INTERVAL: Same	Rio Arriba New Mexico				
AT TOTAL DEPTH: Same	_ 14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,					
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
	6608 GR				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	E C C C C C C C C C C C C C C C C C C C				
TEST WATER SHUT-OFF					

AUG 23 190 (Next Ent results of multiple combined of 24 83)

BUREAU OF LAND OF ON RESOURCE ARE hange on Form 9-330.)

BUREAU OF ON RESOURCE ARE HAND OF OUR HAND O ABANDON\* (other) Replaced Tubing 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* Pulled 1 1/4" Tubing. Found Tubing plugged with Barrum Sulfate 8-3-83 build up on bottom. Laid down 1 1/4" Tubing. Ran used 2 3/8" OD EUE 8rd thrd Tubing to 55891.

Subsurface Safety Valve: Manu. and Type				Set @	Ft.	
18. I hereby certify that the	e foregoing is	true and cor	rect			
SIGNED Charle	s Very	Partitle	Superintendent	DATE	8-18-83	
*		(This space	for Federal or State office us	e)	ACCEPTED FOR	 RECORD
APPROVED BYCONDITIONS OF APPROVAL,		TITL	E	DATE	ACCEPTED TO	

AUG 26 1983

OIL CON. DIV.

FARMINGION RESOURCE AREA

\*See Instructions on Reverse Side

**NMOCC**