

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FNL, 990' FEL, A Sec. 32, T-27-N, R-7-W, NMPM, Rio Arriba County

API # (assigned by OCD)

30-039-06846

5. Lease Number

6. State Oil & Gas Lease #

E-2825-10

7. Lease Name/Unit Name

Harvey A

8. Well No.

1

9. Pool Name or Wildcat

So Blanco Pict. Cliffs

10. Elevation:

RECEIVED
MAY - 9 1997

OIL CON. DIV.
DIST. 3

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☒ Other - Restimulate	

13. Describe Proposed or Completed Operations

4-23-97 MIRU. ND WH. NU BOP. TOO H w/104 jts 1 1/4" tbgr. TIH. SDON.

4-24-97 TIH, tag fill @ 2950'. Blow well & CO. TOO H. SDON.

4-25/27-97 WO weather.

4-28-97 Blow well & CO. TOO H. TIH w/RBP, set @ 2853'. Load hole w/68 bbl wtr. Spot 2 sx sd on RBP. TOO H. TIH w/pkr, set @ 1000'. Attempt to PT csg, failed. Made multiple tool settings. Found csg leaks @ 140-2254'. (Verbal approval to squeeze csg leak when cementing 3 1/2" csg from Johnny Robinson, OCD). TOO H w/pkr. SDON.

4-29-97 Blow well & CO. TIH w/retrieving tool, latch RBP. TOO H. TIH w/6 jts 3 1/2" 9.2# J-55 10RD NUE csg, 74 jts 3 1/2" 7.7# WC-70 10RD NUE csg, set @ 3040'. Pump 30 bbl gelled wtr ahead. Cmt d w/389 sx Class "B" 50/50 poz w/2% gel, 6.5 pps Gilsonite, 0.2% fluid loss, 3% Kcl (494 cu.ft.). Circ 2 bbl cmt to surface. Displace w/1.5 bbl wtr. WOC. SDON.

4-30-97 TIH, tag TOC @ 174'. Drill cmt @ 174-370'. SDON.

5-1-97 Drill cmt @ 370-386'. Blow well & CO. SDON.

5-2-97 Drill cmt @ 386-460'. TOO H. SDON.

5-5-97 TIH, drill cmt to 462'. Receiving metal shavings. Blow well & CO. TOO H. (Verbal approval from Ernie Busch, OCD to plug and abandon well). TIH, perf 4 sqz holes @ 150'. TOO H. Establish circ down csg & out bradenhead. Pump 80 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 5-5-97).

SIGNATURE

Johnny Robinson Regulatory Administrator May 8, 1997

(This space for State Use)

Approved by

Title

DEPUTY OIL & GAS INSPECTOR, DIST. #3

Date

MAY 09 1997