OCT'S 1956

JERRY W. LONG
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Approv	or exbuen n	01 00.					
Indian Agency Jicarilla Tribal							
Contr.	#95,	Tr.	184				
Allottee . J	lcari.	lla	nGn				
Lease No							

NOTICE OF INTENTION TO CHANGE PLANS SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING. NOTICE OF INTENTION TO TEST WATER SHUT-OFF. SUBSEQUENT REPORT OF ALTERING CASING. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL. NOTICE OF INTENTION TO REDRILL OR REPAIR WELL. NOTICE OF INTENTION TO SHOULD OR ACIDIZE. SUBSEQUENT REPORT OF ALTERING CASING. SUBSEQUENT REPORT OF ALTERING. SUBSEQUENT REPORT OF ALTERING. SUBSEQUENT REPORT OF ALTERING. SUBSEQUENT REPORT OF ALTERING. SUBSEQUENT REPORT OF ALTERNAL. AUGUST 17. AUGUST 1	NATION OF INTENTION TO DOLL	SUBSECUIENT DEPORT OF WATER SHIFT OF
SUBSEQUENT REPORT OF ALTERING CASING. OTICE OF INTENTION TO REDRILL OR REPAIR WELL OTICE OF INTENTION TO REDRILL OR REPAIR WELL OTICE OF INTENTION TO SHOOT OR ACIDIZE OTICE OF INTENTION TO HOUL OR ALTER CASING. OTICE OF INTENTION TO PULL OR ALTER CASING. OTICE OF INTENTION TO ABANDON WELL AUGUST 17, 1956 AUGUST 17, 1956 AUGUST 17, 1956 AUGUST 17, 1956 Inne of sec. 35 Clear Section 35 27-N 3-W N.M.P.M. OTICE OF INTENTION TO ABANDON WELL OTICE OF INTENTION TO ABANDON OR REPAIR SUBSEQUENT REPORT OF REPORT OF REPORT. SUBSEQUENT REPORT OF ABANDON METAL SUBSEQUENT REPORT OF ABANDON OR REPAIR SUBSEQUENT REPORT OF REPORT. AUGUST 17, 1956 OTICE OF THE TIME TO		SUBSEQUENT REPORT OF WATER SHOT-OFF
SUBSEQUENT REPORT OF REDRILLING OR REPAIR WELL SUBSEQUENT REPORT OF REDRILLING OR REPAIR SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY OTHER OF INTENTION TO ABANDON WELL SUBSEQUENT REPORT OF ABANDONMENT SUPPLEMENTARY WELL HISTORY SUPPLEMENTARY WELL HISTORY OTHER DATA August 17, 1956 Jicarilla "G" Jicarilla "G" Jine and 990 ft. from E line of sec. 35 LNE\$ Section 35 27-N 3-W N.M. M.		
OTICE OF INTENTION TO PULL OR ALTER CASING OTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) August 17, 1956 Jicarilla "G" August 17, 1956 Jicarilla "G" Ill No. 1 is located 990 ft. from I line and 990 ft. from I line of sec. 25 LNE Section 35 27-M 3-W N.M.P.M. (Rauge) (Meridian) Blanco Ext. Rio Arriba (Mexidian) Blanco Ext. Rio Arriba (State or Excitory) 4 56 Cloud) (County or Subdivision) (State or Excitory) 4 56 ce elevation of the derrick floor above sea level is 7210! ft. DETAILS OF WORK DETAILS OF WORK The restring 2197' of 5½" liner on bottom @ 6200' w/100 ax cement per of liner & 4003'. Temp. survey top of cement & 4968'. Set tainer @ 3918' and cement over top of liner w/150 ax cement. Survey bettom of cement @ 4790'. Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breathers of the company Magnolia Petroleum Company I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Ompany Magnolia Petroleum Company Iddress P. O. Bex 633		
(INEXCATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) August 17, 1956 Jicarilla "G" INO. 1 is located 990 ft. from N line and 990 ft. from E line of sec. 25 LNE; Section 35 27-N 3-W N.M.P.M. (Gibeo, and Sec. No.) Blanco Ext. Rio Arriba (Meridian) (Crist) (County or Subdivision) (Est) c elevation of the detrick floor above sea level is 7210; ft. DETAILS OF WORK DIST. 3 the names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddle line proints, and all other important proposed work) ter setting 2197; of 5½* liner on bottom @ 6200; w/100 ax cement p of liner @ 4003; Temp. survey top of cement @ 4966; Set tainer @ 3918; and cement over top of liner w/150 ax cement. Person of the destrict of the line proposed work) Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Jundany Magnolis Petroleum Company Iddress P. O. Bex 633	OTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
(HENCATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) August 17, 1956 Jicarilla "G" INO. 1 is located 990 ft. from N line and 990 ft. from N line of sec. 25 LNE* Section 35 27-M 3-W N.M.P.M. (Gange) (Meridian) Blanco Ext. Rio Arriba (State or entlery) 4 56 Crokly (Country or Subdivision) (State or entlery) 4 56 ce elevation of the derrick floor above sea level is 7210' ft. DETAILS OF WORK DETAILS OF WORK ter setting 2197' of 5½* liner on bettom & 6200' w/100 sx cement p of liner & 4003'. Temp. survey top of cement & 4968'. Set tainer & 3918' and cement over top of liner w/150 sx cement. essure 1000#. Survey bettom of cement & 4790'. Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breathers. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Sumpany Magnolis Petroleum Company Idress P. O. Bex 633	OTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
Jicarilla "G" Il No. 1 is located 990 ft. from N line and 990 ft. from M line of sec. 35 CHE'S Section 35 27-N 3-W N.M.P.M. CHE'S Section 35 (Twp.) (Rango) (Merdian) (Part) (County or Subdivision) (State or Sectior) 4 56 (Part) (County or Subdivision) (State or Sectior) 4 56 ce elevation of the derrick floor above sea level is 7215' ft. DETAILS OF WORK In points, and all other important proposed casings; indicate muddle in points, and all other important proposed work) Terr setting 2197' of 5½" liner on bottom 6 6200' w/100 ax cement p of liner 6 4003'. Temp. survey top of cement 6 4968'. Set tainer 6 3918' and cement over top of liner w/150 ax cement. Tessure 1000#. Survey bottom of cement 6 4790'. Tested w/1500# Fore and after drilling plugs to 6165' PBTD. Tested 0.K. No breach of the set o	OTICE OF INTENTION TO ABANDON WELL	
Jicarilla "G" Indertila "G" Line is located 990 ft. from Indertina and 990 ft. from Indertina is located 990 ft. from Indertina Indert		
Jicarilla "G" INO. 1 is located 990 ft. from line and 990 ft. from Line of sec. 25 LNEL Section 35 27-N 3-W N.M.P.M. (General Section 35 (Twp.) (Rango) (Meridian) Blanco Ext. Rio Arriba (Meridian) (County or Subdivision) (Est.) (County or Subdivision) (Est.) c elevation of the derrick floor above sea level is 72al5! ft. DETAILS OF WORK Attenumes of and expected dispiths to objective sands above sizes, weights, and lengths of proposed casings; indicate muddle language in grant in goints, and all other important proposed work) ter setting 2197' of 5½" liner on bettom £ 6200' w/100 sx cement p of liner £ 4003'. Temp. survey top of cement £ 4968'. Set tainer £ 3918' and cement over top of liner w/150 sx cement. essure 1000#. Survey bettom of cement £ 4790'. Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breachest in the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Ompany Magnolia Petroleum Company lidress P. O. Bex 633	(INDICATE ABOVE BY CH	ECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
Ine and 990 ft. from him and 990 ft. ft. DETAILS OF WORK Attendance of and expected dupths to objective sands; show alses, weights, and lengths of proposed casings; indicate muddle him and product and 990 ft. ft. DETAILS OF WORK Attendance of and expected dupths to objective sands; show alses, weights, and lengths of proposed casings; indicate muddle him and points, and all other important proposed overs. DETAILS OF WORK Attendance of and expected dupths to objective sands; show alses, weights, and lengths of proposed casings; indicate muddle him are from him and lengths of proposed overs. DETAILS OF WORK Attendance of and expected dupths to objective sands; show alses, weights, and lengths of proposed casings; indicate muddle him are from him and him		August 17, , 1956
Check Section 35 27-N 3-W No More Po Mo (Meridian) Rio Arriba (County or Subdivision) (Est) Re elevation of the derrick floor above sea level is 7216! ft. DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding points, and all other important proposed work) Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Tunderstand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.	Jicarilla "G"	(NI) and (E)
Blanco Ext. Rio Arriba (Comby or Subdivision) (Est) (Comby or Subdivision) (Est) (Comby or Subdivision) (Comby o	ell No. 1 is located 990	ft. from line and 990 ft. from line of sec. 32
Blanco Ext. Rio Arriba (Field) (County or Subdivision) (Est) (County or Subdivision) (County or Subdivision) (Est) (County or Subdivision) (Est) (County or Subdivision) (Est) (County or Subdivision) (State or britary) (State or britary (State or britary) (State or britary (State or britary) (State or britary (Sta	LNEs Section 35 27-	N 3-W N.M.P.M.
(Pield) (County or Subdivision) (Est) (County or Subdivision) (County or Subdivisio	**	
DETAILS OF WORK DETAILS OF WORK Attenumes of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddle in points, and all other important proposed work) The setting 2197' of 5½" liner on bottom @ 6200' w/100 sx sement p of liner @ 4003'. Temp. survey top of cement @ 4968'. Set tainer @ 3918' and cement over top of liner w/150 sx cement. The sesure 1000#. Survey bottom of cement @ 4790'. Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD.		(County of Subdivision) (State of Sertitory)
DETAILS OF WORK ate names of and expected depths to objective ands; show sizes, weights, and lengths of proposed casings; indicate muddle table of impoints, and all other important proposed work) Iter setting 2197' of 5½* liner on bettom @ 6200' w/100 ax cement p of liner @ 4003'. Temp. survey top of cement @ 4968'. Set tainer @ 3918' and cement over top of liner w/150 ax cement. **essure 1000#. Survey bettom of cement @ 4790', Tested w/1500# **Fore and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. **ARMINITY** **A	• •	(Est) 4 50
DETAILS OF WORK ate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddle that on ing points, and all other important proposed work) ter setting 2197' of 5½" liner on bettom @ 6200' w/100 ax sement p of liner @ 4003'. Temp. survey top of cement @ 4968'. Set tainer @ 3918' and cement over top of liner w/150 ax cement. essure 1000#. Survey bettom of cement @ 4790', Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. Ompany Magnolia Petroleum Company Iddress P. O. Bex 633	e elevation of the derrick floor abov	re sea level is 7216° ft. OIL CON. CON
DETAILS OF WORK The names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate muddle in points, and all other important proposed work) Iter setting 2197' of 5½" liner on bettom @ 6200' w/100 sx cement point liner @ 4003'. Temp. survey top of cement @ 4968'. Set stainer @ 3918' and cement over top of liner w/150 sx cement. Survey bettom of cement @ 4790'. Tested w/1500# fore and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and after drilling plugs to 6165' PBTD. Tested O.K. No breachest and that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced. The point of the plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		DIST. 3
There setting 2197' of 5½" liner on bottom @ 6200' w/100 ax cement op of liner @ 4003'. Temp. survey top of cement @ 4968'. Set otainer @ 3918' and cement over top of liner w/150 ax cement. Tessure 1000#. Survey bottom of cement @ 4790'. Tested w/1500# of fore and after drilling plugs to 6165' PBTD. Tested 0.K. No break and after drilli		
There setting 2197' of 5½" liner on bottom @ 6200' w/100 ax cement op of liner @ 4003'. Temp. survey top of cement @ 4968'. Set otainer @ 3918' and cement over top of liner w/150 ax cement. Tessure 1000#. Survey bottom of cement @ 4790'. Tested w/1500# of fore and after drilling plugs to 6165' PBTD. Tested 0.K. No break and after drilli		
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. ompany Magnolia Petroleum Company ddress P. O. Bex 633	_	ds; show sizes, weights, and lengths of proposed casings; indicate mudding ichs. commits, and all other important proposed work)
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. ompany Magnolia Petroleum Company ddress P. O. Bex 633	ter setting 2197' of 5½' p of liner @ 4003'. Tentainer @ 3918' and cementers are because by	ds; show sizes, weights, and lengths of proposed casings; indicate muddle is he, can the same of the control of
I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced. ompany Hagnolia Petroleum Company ddress P. O. Bex 633	ter setting 2197' of 52' op of liner @ 4003'. Ter taimer @ 3918' and cemen ressure 1000#. Survey be	ds; show sizes, weights, and lengths of proposed casings; indicate muddle is he can be to me and all other important proposed work) ** liner on bettom @ 6200' w/100 sx cement mp. survey top of cement @ 4968'. Set nt over top of liner w/150 sx cement. ** ottom of cement @ 4790'. Tested w/1500# plugs to 6165' PBTD. Tested O.K. No break
ddress P. O. Bex 633	Tter setting 2197' of 5½'op of liner @ 4003'. Tentainer @ 3918' and cementes are 1000#. Survey be	ds; show sizes, weights, and lengths of proposed casings; indicate muddle is he, can the same of the control of
	ter setting 2197' of 5½'s p of liner @ 4003'. Tentainer @ 3918' and cementessure 1000#. Survey before and after drilling	display sizes, weights, and lengths of proposed casings; indicate muddles is he can be to me a size of the content of the content over top of cement @ 4968'. Set not over top of liner w/150 ex cement. Tested w/1500# plugs to 6165' PBTD. Tested O.K. No brest ARMIRCICE, ALC.
Midland, Texas By R. T. GERMAN,	ter setting 2197' of 52' p of liner @ 4003'. Tentainer @ 3918' and cementessure 1000#. Survey be fore and after drilling	ds; show sizes, weights, and lengths of proposed casings; indicate mudding the contents, and all other important proposed work) "liner on bettom @ 6200' w/100 sx cement mp. survey top of cement @ 4968'. Set nt over top of liner w/150 sx cement. ettom of cement @ 4790', Tested w/1500# plugs to 6165' PBTD. Tested O.K. No break ARMIRELE.
R. T. GERMAN,	ter setting 2197' of 52' p of liner @ 4003'. Tentainer @ 3918' and cementessure 1000#. Survey before and after drilling	ds; show sizes, weights, and lengths of proposed casings; indicate mudding the cases, and all other important proposed work) "liner on bettom @ 6200' w/100 sx cement mp. survey top of cement @ 4968'. Set nt over top of liner w/150 sx cement. ottom of cement @ 4790'. Tested w/1500# plugs to 6165' PBTD. Tested O.K. No break plugs to 6165' PBTD. Tested O.K. No break approval in writing by the Geological Survey before operations may be commenced. Company
	ter setting 2197' of 52's p of liner @ 4003'. Tentainer @ 3918' and cementessure 1000#. Survey before and after drilling of the standard drilling of the set of the s	ds; show sizes, weights, and lengths of proposed casings; indicate mudding the cases, and all other important proposed work) "liner on bettom @ 6200' w/100 sx cement mp. survey top of cement @ 4968'. Set nt over top of liner w/150 sx cement. ottom of cement @ 4790'. Tested w/1500# plugs to 6165' PBTD. Tested O.K. No break plugs to 6165' PBTD. Tested O.K. No break approval in writing by the Geological Survey before operations may be commenced. Company

•