OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

ocarion		OIL COMPAN	IY OF CALIFORN DBA UNUCAL 27N	IIA Lesse Rge	RINCO		Coun	Wo No		
	NAME OF RESERVOIR OR POOL				TYPE OF PROD.		METHOD OF PROD.		PROD, MEDIJM (Top. or Coq.)	
Upper Completion		MESA VERD	GAS		FLOW		TBG.			
Completion DAKOTA				GAS			FLOW		TBG.	
			PRE-FLO	W SHUT-IN PI	RESSURE	DATA				
Upper Hour, date shut-in Length of time shut-in JUNE 04, 1995 10:00AM 3 Lever Hour, date shut-in Length of time s				B DAYS	St press, paig CSG. 400 TBG. 410 St press, paig TBG. 685			Stabilized? (Yes or Ne) NO Stabilized? (Yes or Ne) NO		
Conumenced of O	New, date	JUNE 07.	. 1995 IU:1:	FLOW TEST				1.00		
TIME LAPSED TIME (from, date) SINCE®		PRESSURE Upper Completion Lower Completion		Zone producing (Up) PROD. ZONE		DEFF OF LOWER LOWER				
06/08		24 HRS.	CSG. 400 TBG. 410 CSG. 405	TBG. 130	 	o	Q = 295			
06/09	/95	48 HRS.	TBG. 410	TBG. 210	59	·	Q = 518	MCF/	′Q	
										· ·
									- · · · · · · · · · · · · · · · · · · ·	
Production 1			D based on	Bbls. in	.	_ Hours_			GOR	
G25:			- <u>-</u>	D; Tested thru				000		
				ST SHUT-IN PI		,				
Compretion	r, dale shu		Length of time shut-	in .	SI press. poi	•		Slabilized	7 (Yes or He)	
Leaver Completion Langin of time shut-in				in .	St press, parg Stabilized? (Yes				7 (Yes or Ne)	

(Continue on reverse side)

om colo

TEU .. IEM I.U. Z

Commenced at theur, dat	o) + +		Zana preducing (Upper or Lowert				
TIME (hour, date)	LAPSED TIME SINCE ##	PRES Upper Completion	SURE Lever Completion	PROD. ZOME TEMP.	REMARKS		
							
					· · · · · · · · · · · · · · · · · · ·		
			:	·			
Production rate d	luring test	· · · · · · · · · · · · · · · · · · ·					
	•	D based on	Rhie i	B Hong	Grav GOR		
					— — —·		
(Jas:		МС	FPD: Lested Uni	I (Ourse of Wese	r):		
Remarks:							
							
I hereby certify t	hat the informat	ion herein contai	ned is true and o	complete to the be	st of my knowledge.		
Approved	al Pel	inem	19	Operator UNIO	N OIL COMPANY OF CALIFORNIA DBA		
Approved	il Construction	Division		By has	Lak- Liss		
	JUN 16	1995		Sand	ra K. Liese eral Clerk		
Ву	DEPUTY OIL & GAS	INSPECTOR		11uc			
Tide	DET OTT OIL & GITO			Date June	2 13, 1995		

NORTHWEST NEW MEDICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply complexed well within seven days after octual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such test shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the rubing have been distructed. Tests shall also be taken as any time that communication is suspected or when requested by the Osinian.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in usual the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be short-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced 2000 shall remain abut-in while the 2000 which was previously shut-in is produced.

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minuse intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time dusing each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test date.

24-hour oil zone tests: all pressures, thoughout the entire test, shall be communically measured and recorded with recording pressure gauges the accuracy of which must be directed at least twice, once at the legislating and once at the end of each test, with a deadweight pressure gauge. If a well is a gue-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas some.

8. The results of the above-described tests shall be filed in suplicate within 13 days after completion of the test. Tests shall be filed with the Aster District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 18-01-78 with all dendweight pressures indicated thereon as well as the flowing amperatures (gas zones only) and gravity and GOR (oil zones only).