STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page Revised 10/01/7

be used for reporting packer leakage tests In Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perat	·	ON OIL COMPA	ANY OF CALIFO DBA UN		RINCON UNIT		Wo	
atio Well	n : Unit	K Sec. 29			6W	Con	anty	RIO ARRIBA
		NAME OF RESERV	OIR OR POOL	TYPE OF (OII or	1	METHOD OF PRO (Flow or Art. Lift)		PROD. MEDIUM (Tog. or Cog.)
pper pletie	n	BLANCO MES	SA VERDE	GAS		FLOW	FLOW	
wer pietio	6	BASIN DAK	ОТА	GAS	FLOW T		TUBING	
			PRE-FI	OW SHUT-IN I	PRESSURE	DATA		
per pletio	Hour, date shul-in Length of time shut-				81 press, paig			(Yes or No) NO
wor pietie	Hour, date	shul-in IL 14, 1996	Length of time at 10:00AM	3 DAYS	SI press. psig TBG. 440		Stabilized? (Yes or No) NO	
				FLOW TEST	'NO. 1			
ience	d at (hour, da	•••• APRIL 1	7, 1996 10:	10AM		Juding (Upper er Lowerk	LOWER	
TIME Grour, date)		LAPSED TIME SINCE#	PREI Upper Completion	Lower Completion	PROD.		REMARKS	
04/	18/96	24 HRS	CSG. 420 TBG. 415	TBG. 260	50°	Q	= 96 M	ICF/D
04/19/96		48 HRS.	CSG. 425 TBG. 420	TBG. 240	44°) = 91 MCF/D	
	·							
	on rate di	•		·			•	
	<u></u>	BOPI	D based on	Bbls. in	1	Hours G	irav	GOR
		<u> </u>	MCF	PD; Tested thru	(Orifice or	Meter):		
 ,				ST SHUT-IN PI	RESSURE I			
er Hon	<u> </u>		Length of time shu		Si press. psig		Stabilized? (
r er letion	Hour, date st	rut-in	Length of time shu	t-in	SI press. pelg		Stabilized? (Yes or No)	
				•	•	回回回回	aner.	
-			•					

APR 3 0 1999 🔑

(Continue on reverse side)

OU CON. DR

FLOW TEST NO. 2

PRESSURE

Zone producing (Upper or Lower):

(hour, date)	SINCE ##	Upper Completion	Lower Completion	TE	MP.	REMARKS	1
							1
							1
·							1
			**************************************				+
		2-P-2-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-					
<u> </u>	<u> </u>				. (
Production rate d	luring test						
Oil:	BOPE	D based on	Bbls. in		_ Hours	Grav GOR	•
Gas:		MCFF	D: Tested thru (Orifice o	r Meter):		
I harabu carrifu el	ner the information	- harrisi	J : 1	•			
	nat the information						TIMC
ApprovedA New Mexico O	hany Robins I Conservation Di	vision	. 19 Op	erator ,	ONTON C	OIL COMPANY OF CALIFORNIA DBA	UNC
	APR 3 0 1996	6	Ву		R.L. Ca	Jame :	
By	UTY OIL & GAS INSP	PECTOR				tion Foreman	
Title	OTT OIL G GROTHOT		D ₂	te	April 2	25, 1996	

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been distrubed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut in while the zone which was previously shut in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Atter District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

RLC/sk1

Commenced at (hour, date) * *

LAPSED TIME

TIME