

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Albuquerque

Lease No. 379301

Unit 1/4 sec. 30

Lincoln Unit

Box 916

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

October 7, 1951

Well No. 29 is located 190 ft. from N line and 299 ft. from W line of sec. 30

1/4 sec. 30 (1/4 Sec. and Sec. No.) T1N (Twp.) 6E (Range) 104E (Meridian)
So. Alamo Mgt. Canyon Mt. (Field) Alamo (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is 6711 ft. 00

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drill 1 1/4 inch rotary hole to 110 feet. Set 100 feet of 10 1/4 inch surface casing. Circulate out with 100 sacks.

Drill 1 1/4 inch hole to 1100' or top of fractured cliff - set 20, 7 inch casing with 100 sacks regular cement.

Drill 1 inch hole with cable to 1s from 1100 to 1200 feet.

Shoot open hole, tamped, with 300 quarts Nitro Gel.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Alph A. Johnston

Address Box 123

Albuquerque, New Mexico

By

Title

James W. Copeland
James W. Copeland
Capt.