
Form 9-381 a (Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office .	Santa 1	ře
Lease No	079364	
Init	Rincon	

Subsequent Report of Abandonment Suprementary Well History Water Fract. Well No. 135(MD) is located 1160 ft. from No. 1250 ft. from Expline and 1750 ft. from Expline No. 125(MD) is located 1160 ft. from No. 1250 ft. from Expline and 1750 ft. from Expline No. 125(MD) is located 1160 ft. from No. 1250 ft. from Expline No. 1250 ft. from Explication No. 1250 ft. from Expline No. 1250 ft. from Expline No. 1250 ft. from Expline No. 1250 ft. from Explication No. 1250 ft. from Expline No. 1250 ft. from Expline No. 1250 ft. from Explication No. 1250 ft. from	SUBSEQUENT REPORT OF WATER SHUT-OFF	
Subsequent report of Re-Drilling or Repair well notice of intention to Shoot or Acidize subsequent report of Re-Drilling or Repair Notice of intention to Pull or Alter Casing. Notice of intention to Pull or Alter Casing. Notice of intention to Abandon well. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, or other DATA) March 1 Well No. 1-35 (MD) is located 1160 ft. from Notice of Intention to Abandon well. NE/4 Sec. 29 27N 6W N.M.P.M. (K Sec and Sec. No.) (Twp.) (Range) Blunce M.V. & So. Blunco Dak. Ext. Rio Arriba New Mor. (Field) (County or Subdivision) (State or Territe The elevation of the derrick floor above sea level is 6606 ft. DETAILS OF WORK State names of and expected depths to objective sands, show sizes, weights, and lengths of proposed casings; Indicate in points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fracture Perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 a 40,000 sand. BD pr. 2600 nm.c. pr. 2300 nm.c. pr. 2300 nm.c. pr. 2100 nm.c. pr. 2100 nm.c. pr. 2100 nm.c. pr. 3000 nm.c. pr. 2100 nm.c. pr. 3000 nm.c. pr. 2100 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300 nm.c. pr. 300 nm.c. pr. 210 nm.c. pr. 300	NG	
Subsequent report of Abandonment supplementary well history water fractured (Field) Notice of intention to Abandon well. (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE AND ASSOCIATION, NATURE OF REPORT, NOTICE AND ASSOCIATION, NATURE OF REPORT, NOTICE AN		
NOTICE OF INTENTION TO PULL OR ALTER CASING. NOTICE OF INTENTION TO ABANDON WELL (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (March 1 (March 1 (Meridian) New Merick (Meridian) (State or Territe March March (Meridian) (State or Territe March March March (Meridian) (State or Territe March March March (Meridian) (State or Territe March March March March (Meridian) (State or Territe March Marc	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.	
March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT NATURE OF REPORT NOTICE, OR OTHER DATA (INDICATE ABOVE BY CHECK MARK NATURE OF REPORT NATURE OF REPOR		
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) March 1 Well No. 135(MD) is located 1160 ft. from No. 1150 ft. from Eline NE/4 Sec. 29 27N 60 N.M.P.M. (K Sec. and Sec. No.) (Twp.) (Range) (Meridian) Blance N.V. & So. Blanco Dak. Ext. Ric Arriba (Meridian) The elevation of the derrick floor above sea level is 660.6 ft. DETAILS OF WORK State names of and expected depths to objective and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fracture perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# seand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-94 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations m. Address. Box 297	x	
March 1 Well No. 135(MD) is located 1160 ft. from No. 1750 ft. from Edition NE/4 Sec. 29 27N 60 N.M.P.M. (4 Sec. and Sec. No.) (Twp.) (Range) (Meridian) Blance M.V. & So. Blanco Dak. Ext. Rio Arriba New Meridian (Pied) The elevation of the derrick floor above sea level is 6606 ft. DETAILS OF WORK State or Territe in prints, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-72 w/41,0 a 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff House ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BPM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) is 1 faso Natural C.S. Company. Address Box 997		
/ell No. 135 (MD) is located 1160 ft. from No. 1750 ft. from Ellino NE/4 Sec. 29 27N 6W N.M.P.M. (4) Sec. and Sec. No.) (Twp.) (Range) (Meridian) Blance M.V. & So. Blanco Dak. Ext. Ric Arriba New Mericing of the elevation of the derrick floor above sea level is 6666 ft. DETAILS OF WORK tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fracture Perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations me Company. All Paso Natural C. S. Company. address. Box 997	·	
NE/4 Sec. 29 27N 6W N.M.P.M. (W Sec and Sec. No.) Blance M.V. & So. Blanco Dak. Ext. Ric Arriba (Field) (County or Subdivision) Class of the elevation of the derrick floor above sea level is 6606 The elevation of the derrick floor above sea level is 6606 DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates in points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 is 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 274 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations maddress. Box 997	1 , 19 60	
NE/4 Sec. 29 27N 6W N.M.P.M. (W Sec and Sec. No.) Blance M.V. & So. Blanco Dak. Ext. Ric Arriba (Field) (County or Subdivision) Class of the elevation of the derrick floor above sea level is 6606 The elevation of the derrick floor above sea level is 6606 DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates in points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 is 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 274 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations maddress. Box 997	e of sec. 29	
Blance M.V. & So. Blanco Dak. Ext. Ric Arriba New Meridian New Meridian M.V. & So. Blanco Dak. Ext. Ric Arriba New Meridian New Meridian Meridian New Meridian Meridian (County or Subdivision) (State or Territy New Meridian) (State or Territy New Meridian	771	
Blance M.V. & So. Blanco Dak. Ext. Ric Arriba New Mer. (Field) (County or Subdivision) (State or Territor) The elevation of the derrick floor above sea level is 6606 ft. DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates in points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations maddress. Box 997	- / c $t0$	
(County of Subdivision) (State of Territoria) (Relevation of the derrick floor above sea level is 6606 ft. (DETAILS OF WORK) (State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate ing points, and all other important proposed work) (2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 be 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff House ft.) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/f) I understand that this plan of work must receive approval in writing by the Geological Survey before operations maddress. Dox 997	xido	
DETAILS OF WORK itate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 balls and 1 set of 10 balls at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/f I understand that this plan of work must receive approval in writing by the Geological Survey before operations me Company 11 Paso Natural C 3 Company address Box 997	ory)	
DETAILS OF WORK State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 balls and 1 set of 10 balls at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BPM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/f I understand that this plan of work must receive approval in writing by the Geological Survey before operations more company. It has a Natural C. 3 Company. Address. Box 297	No. 1	
tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 to 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 be 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations me company fl 2000 Natural C. S. Company. dddress Box 997	1 To 10 10 11	
tate names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicates ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 at 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 be 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff Hou ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BFM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/ft) I understand that this plan of work must receive approval in writing by the Geological Survey before operations moments. Company 11 Paso Natural C. 3 Company. dddress Box 997	1	
ing points, and all other important proposed work) 2-4-60 Total Depth 7678'. Bridge plug at 7140'. Water fractured perf. int. (2 DJ/ft) at 5382-96; 5403-16; 5430-36; 5472-78 w/41,0 & 40,000# sand. BD pr. 2600#, max. pr. 2300#, avg. tr. pr. 1800# Flush 11,130 gallons. Dropped 1 set of 20 balls and 1 set of 10 b 2-4-60 Temporary bridge plug at 4930'. Water fractured Cliff House ft) at 4848-54 w/10,234 gallons water and 10,000# sand. BD pr. 27 avg. tr. pr. 3000#. I.R. 19.9 BPM. Flush 8400 gallons. 2-8-60 Temporary bridge plug at 4930'. Perf. Cliff House (4 DJ/f I understand that this plan of work must receive approval in writing by the Geological Survey before operations me company if Paso Natural C.3 Company diddress. Box 997	mudding jobs, cement-	
Company <u>El Faso Natural C s Company</u>	OO galloas wat I.R. 46.9 BP alls for 3 sta se perf. int. OO#, max. pr.	
Farmington, New Mexico By ORIGINAL SIGNED R.I		
Title Petroleum Engine	er	