

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency

Contr. #75-2007 / 104

Allottee

Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

September 7, 1958

RECEIVED
SEP 10 1958
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO


Well No. 8 is located 990 ft. from N line and 990 ft. from E line of sec. 26
NE 1/4 Sec. 26 27N 3W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco NV & Unisig. FC Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 7214 ft. MSL.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Set 2255' of 5" liner on bottom @ 6210, cemented w/200 slm. 64 Gal + 1/2 Flueoil sl. + 25 slm. next. Top of liner @ 4005'. Plug down 4715 PM, 1 September 4, 1958. Top of cement @ 4005'. WAS 24 hours. Set top 5" liner and 1-1/8" Csg. w/0000 for 30 minutes, hold OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Mexican Petroleum Company

Address P. O. Box 2406
Albuquerque, New Mexico

By [Signature]
Title District Superintendent