STATE OF NEW MEXICO

ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests

in Southeastern New Mexico

NORTHWEST NEW MEXICO PACKER-I FAKACE TEST

	JNION O	IL OF CALIFOR	RNIA/dba		Lease	RINCON	UNIT	E LESI	Well No. 1	37
Location of Well: Unit	<u> </u>	Sec. 24	Twp.	27N	Rge	07W		Cour	nty RIO AF	RIBA
Upper		NAME OF RESER	RVOIR OR	POOL	4	OF PROD. il or Gas)		METHOD OF F (Flow or Art.		PROD. MEDIUM (Tbg. or Csg.)
	LANCO	MESA VERDE			GAS		FLO	N		TUBING
ľ	ASIN DA	KOTA			GAS		FLOV	N		TUBING
		<u>.</u>		PRE-FLO	W SHUT-I	N PRESS	URE DATA			
	date shut-i	n	ı	Length of time shut	:-in		l press. psig		Stabilized? ()	es or No)
	0: a.m. 7/24/97		ı	5 DAYS			SG 205			
i	date shut-i	n	i	Length of time shut	-in	i	BG 205		Yes	
): a.m.	07/24/97		5 DAYS	 -		I press. psig BG 370		Stabilized? (Y Yes	es or No)
					FLOW TES	T NO. 1				
Commenced at (hou	ır, date)*	3:20 p.m.	07/29/9				one producing (Upp	er or Lower)* LO	wer	
TIME (hour, date)		LAPSED TIME SINCE*		PRESS		-4:	PROD. ZONE		REMAR	KS
9: a.m.				SG 215	Lower Compl	etion	TEMP.			
07/30/97	ļ	24 hrs		BG 215	TBG 140	59	9°°	Q = 162	mcf	
9:30 a.m.			0	SG 215				1 - 10		
07/31/97		48 hrs	T	BG 215	TBG 160	62	2°	Q = 174	mcf	
								an l	CE	
		-						MA	UG 13	387
									1 4000	
	<u>!</u>				<u> </u>	İ		(O)	(الماز@B) لم معالمات	.~
Production rate du	ring test							the second		
Oil:		ВОР	D based o	on	Bbls. i	n	Hours.	Gra	v	GOR
Gas:		·		MCFPD; Teste	ed thru (Orifice o	or Meter):				
			M	IID-TEST SHU	T-IN PRES	SURE DA	NTA			
Hour, da Upper Completion	ate shut-in			Length of time shut-ir	n	SI F CS TB			Stabilized? (Ye.	s or No)
Lower Hour, da	ate shut-in			Length of time shut-in	1	sı r TB	oress. psig		Stabilized? (Yes	s or No)
				(Co	ontinue on re	verse side	e)			

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST FLOW TEST NO. 1

Commenced at (hour, date)*				Zone producing (Upper or Lower)* UPPER			
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE	REMARKS		
(hour, date)	SINCE*	Upper Completion	Lower Completion	TEMP.			
		CSG					
		TBG	TBG				
		CSG					
		TBG	TBG				
		CSG					
		TBG	TBG				
	1		1				

:	BOPD based on		Bbls. in	Hours.	Grav.	GOR _
		MCFPD; Tested thru	(Orifice or Meter):			
arks:						
						
reby certify that the	information herein contained is	s true and compete to the	he best of my know	ledge.		
•	information herein contained is	s true and compete to the	he best of my know Operator	_	CALIFORNIA/dba UN	OCAL
proved	information herein contained in servation Alliaion 8 1997	. 19	Operator	UNION OIL OF		OCAL
proved		19	Operator	UNION OIL OF	Jaket	OCAL

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shul-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No.1, one zone of the dual completion—shall be produced at the normal rate of production while the other zone remains shut-in. Such test—shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No.1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No.1 except

that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.

- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours test: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as a required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10 01 78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)