

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Page 2

FORM APPROVED
Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

Lease Designation and Serial No

SF-079-366

Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

UNITED STATES MEXICO If Unit or CA, Agreement Designation

Type of Well
☐ Oil ☒ Gas ☐ Other
☐ Well ☐ Well

Name of Operator

Union Oil Company of California

Address and Telephone No

8. Well Name and No.

Rincon Unit #117

9. API Well No.

30-039-06976

10. Field and Pool, or Exploratory Area

11. County or Parish, State

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☒ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11/28 PU & RIH W/ 4-3/4" WASH SHOE, 5' WASH PIPE SUB W/ JUNK CATCHER, JUNK BASKET, 3-1/8" CO'S & 74 JTS 2-3/8" TBG. COT OVER CMT RET @ 2535'. PUSHED RET TO CIBP @ 2950'. POH, REC'D COIL SPRING & 4" OF BTM BRASS MANDREL, BTM OF SHOE PLUGGED W/ RUBBER. RIH W/ BAKER MODEL "C" 5-1/2" RET BP & MODEL "C" FULL BORE PKR. SET RBP @ 2627'. TSTD PLUG TO 1000 PSI, OK. SET PKR @ 2502'. ATTEMPTED TO PUMP INTO SQUEEZE PERFS @ 2570'. PRESS TO 1500 PSI, BLED TO 1100 PSI IN 2 MIN. REPEATED 5 TIMES W/ SAME RESULTS. SWI, SDON.

11/29 14 HR SITP & CP: SL VAC. RIH TO REL RBP @ 2627' - HAD PBLMS REL RBP. SPA 2627' - P-TSTD TO CIBP @ 2950-800#, OK. TO RESET RBP ABOVE SQZ PERFS @ 2570 IN 5 PLACES - N/G. SPA 2180 & P-TSTD TO SURF TO 800#, OK. POH W/ PKR & RBP - HAD 6-10M# OSW DRAG & FOUND DAMAGED SLIP ASSY. SDON.

11/30 18 HR SITP O. PU & RIH W/ BAKER 5-1/2" MODEL "C" RBP & MODEL "C" FULL BORE PKR. SET RBP @ 2627' & TSTD TO 1500 PSI. SET PKR @ 2533' W/ BY-PASS OPEN. SPTD 300 GALS 15% HCL + 0.5 GAL CLAY MASTER, 0.5 GAL AQUA FLOW & 1.5 GAL XR-21 TO BTM OF PKR. ACIDIZED SQ PERFS @ 2570. STARTING PRESS 1500 PSI-BLED TO 1000 PSI IN 4 MIN. BROKE TO 1.5 BPM @ 1500 PSI. ISIP 1400# (5) 1300#, (10) 1250#, (15) 1200#, (30) 1150#. TLTR 20.5 BBLS. SERVICE BY WESTERN. SWBD 24 BF IN 6 RUNS. FINAL FL @ 2400'. RIH TO RBP @ 2627'. REV OUT 2/ 25 BFW. POH W/ RBP & PKR TESTING GOR CSG LEAKS. FOUND CSG LEAKS FROM 2254-2378'. LD PKR & RBP. RIH W/ BAKER MODEK K-1 5-1/2" MECH. SET CMT RET. SET RET @ 2533'. SWI, SDON.

I hereby certify that the foregoing is true and correct

Signed Walter B. Smith

Title Drilling Clerk

Con'ta Pg. 3

Date 12-6-90

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any

Title _____

Date _____

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side