

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

Lease Designation and Serial No. SF-079366
Indian, Allottee or Tribe Name
CA. Agreement Designation
Well Name and No. Rincon Unit #117
API Well No. 30-039-06976
Field and Pool, or Exploratory Area
Country or Parish, State

SUBMIT IN TRIPLICATE

Type of Well: Oil Well, Gas Well, Other
Name of Operator
Address and Telephone No.
Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec. 21, T27N, R6W

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

Table with columns: TYPE OF SUBMISSION (Notice of Intent, Subsequent Report, Final Abandonment Notice), TYPE OF ACTION (Abandonment, Recompletion, Plugging Back, Casing Repair, Altering Casing, Other), and Change of Plans (New Construction, Non-Routine Fracturing, Water Shut-Off, Conversion to Injection, Dispose Water)

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12/18 18 HR SITP & SICP SLT VAC. RU WESTERN. STUNG OUT OF CMT RET & SPTD 50 SX CL "B" + 1.1% CF-18 TO 1 BBL ABOVE RET. STUNG INTO RET & SQUEEZED PERFS @ 2570' @ 1/4 BPM @ 250-1500 PSI. DISPL 40 SX INTO PERFS. STUNG OUT OF RET & REVERSED CLEAN. POH TO BTM OF CSG LEAKS @ 2378'. SPTD 50 SX CL "B" + 1.1% CF-18. POH W/ 10 STDS TBG& REVERSED CLAN. SQUEEZED CSG LEAKS 2254-2378' TO 1000 PSI-HELD 20 MIN OK. DISP 15 SX CMT INTO HOLES. POH W/ 2-3/8" TBG & RET STINGER. CLOSED BLIND PAMS & RE-PRES 5-1/2" CSG TO 1000 PSI.
12/19 WELLHEAD, BOP & MUD PIT FROZEN UP. SICP TSTM. RIM W/ 4-3/4" BIT, 6 3-1/8" DC'S & 60 JTS 2-3/8" TBG. TAGGED CMT @ 2067'. DRLD SOFT CMT 2067-2077' & HARD CMT 2077-2256'. PRESS TSTD CSG TO 800 PSI. OK. SWI, SDON.
12/14 SITP & SICP O. DRLD HARD CMT 2256-2371', SOFT CMT 2371-2375', & CMT STRGRS 2375-2388'. PRESS TSTD CSG TO 800 PSI @ 2287', 2319', 2350' & 2388', OK. FELL FREE @ 2388'. RIM TO CMT RET @ 2533'. DRLD OUT RET @ DRLD TO 2539'. PIECE OF RET ROLLING UNDER BIT. CIRC CLEAN. SWI, SDON.
12/16 SITP & SICP O. DRLD HARD CMT 2539-2576', FIRM CMT 2576-2587'. FELL FREE @ 2587'. TSTD SQUEEZE PERFS @ 2570' TO 800 PSI. OK. RIM TO CIBP @ 2950'. DRLD ON CIBP 5 HRS. DID NOT BREAK THRU. CIRC CLEAN. SWI, SDON.

I hereby certify that the foregoing is true and correct.
Signed: Charlotte Peterson Title: Dring Clerk Date: 12-11-90
Approved by: Conditions of approval, if any Title Date

Title 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

\*See Instruction on Reverse Side