

		X	

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **Santa Fe**
Lease No. **079366**
Unit **Bincon Unit**

1 1958

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOYING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	
	Water Prac. X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 25, 1958

Well No. **108(MD)** is located **1750** ft. from **[N]** line and **1750** ft. from **[E]** line of sec. **19**
NE **Sec. 19** **27N** **6W** **N.M.P.M.**
(¼ Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M.V. **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6523** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

11-22-58. Total Depth 7532'. Temporary bridge plug at 7250'. Water fractured Point Lockout perforated intervals 5012-22; 5064-80; 5172-92; 5308-38; 5346-52; 5410-24 (2 SFF) with 66,400 gallons water and 60,000# sand. B.D.P. None, max. pr. 3600#, avg. tr. pr. 1250-1000-1600-2350-2600#. I.R. 48.4 B.P.M. Flush 10,400 gallons. Injected 5 sets balls (30 balls/set).
11-22-58. Total Depth 7532'. Temporary Bridge Plug at 4975'. Water fractured Cliff House perforated intervals 4748-78 (2 SFF) with 54,000 gallons water and 40,000# sand. B.D.P. 3000#, max. pr. 3000#, avg. tr. pr. 1700-1850#. I.R. 55.4 B.P.M. Flush 10,400 gallons. Injected 1 set of 15 balls. Shot 4-way squeeze gun at 4730' before perforating and fracing. Pressured up to 3500 psi--held O.K.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

Farmington, New Mexico

By **Original Signed R. G. MILLER**

Title **Petroleum Engineer**