Page Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

| Operator | | N OIL COMPA | | DE CALIFO | | A Lease _ | RINO | CON UNI | Τ | No | |
|--|----------------------------|-----------------------|-----------------------|--|--------|---------------------|----------------|---------------|----------------|--|---|
| Location of Well: | Unit A | Sec21 | | | | Rge | 6W | | Cou | nty | RIO ARRIBA |
| | NAME OF RESERVOIR OR POOL | | | | | TYPE OF | | METHOD OF PRO | | | PROD, MEDIUM (Tog. or Cag.) |
| Upper Completion | · | | | | s | GAS | | FLOW | | | TRG |
| Completion BLANCO MESA VERDE | | | | | | GA: | 5 | FLOW | | | TBG |
| | | | | PRE-F | low | SHUT-IN F | | | | | |
| Upper Completion | pletion APRIL 07, 1996 11: | | | Length of time | 3 [| DAYS SI press. paig | | TBG 195 | | Stabilized? (Yes or No) N() Stabilized? (Yes or No) | |
| Lower Completion | Lower | | | OAM 3 DAYS . | | DAYS . | TBG 270 | | 70 | NO | |
| | | | | | I | LOW TEST | NO. 1 | | | | |
| Consmenced | at (hour, dat | •ı≉ APRIL 1 | 0,1 | 996 11: | 30AN | 1 | Zone pro | ducing (Upp | w or Lowerk LO | WER | |
| TIME (hour, date) | | LAPSED TIME SINCE# | | | | ower Completion | PROD. TEM | | REMARKS | | IARKS |
| 04/11/96 | | 24 HRS | | | TE | 3G 125 | 58° | | <u> </u> | Q = 208 MCF/D | |
| 04/12/96 | | 48 HRS | CSG 205 TBG 205 TI | | | BG 110 | 62° | 62° Q = | | = 146 MCF/D · | |
| | | | | | | | | | *** | | |
| _ | | ·. | | | | | | | | - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | |
| | | | | | | | | | | | |
| | | | | | | | | | • | | <u>, , , , , , , , , , , , , , , , , , , </u> |
| Productio | n rate du | uing test | | | | • | | | | • | 7 V |
| Oil: | | BOF | D bas | ed on | | Bbls. in | | Hours. | G | rav | GOR |
| Gas: | | | | мс | FPD; | Tested thru | (Orifice o | r Meter): | | | |
| | | | | MID-T | EST | SHUT-IN PF | ESSURE 1 | DATA | | | |
| Upper Hour, date shut-in . Length of time shut-in Completion | | | | | hul-in | | SI press, paig | | | Stabilized? (Yes or No) | |
| | | | | ength of time shut-in | | SI press, paig | | | Stabilized? | (Yes or No) | |

(Continue on reverse side)

FLOW TEST NO. 2

Zone producing (Upper or Lower):

| TIME | LAPSED TIME | PRES | SURE | PROD. ZONE | | |
|-------------------|-------------------|--------------------|-------------------|--------------------|--|--|
| (hour, date) | SINCE ** | Upper Completion | Lower Completion | TEMP. | REMARKS | |
| | | | | | | |
| | | | | | · | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | - | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | <u>L</u> | <u> </u> | 1 | | | |
| oduction rate d | uring test | | | | | |
| | | | | | | |
| il: | BOP | D based on | Bbls. in . | Hours. | Grav GOR | |
| ••• | | 1/07 | | | | |
| u: | | MCFF | 'D: Tested thru (| Orifice of Meter): | • | |
| ·marke· | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| nereby certify th | at the informatio | on herein containe | d is true and com | plete to the best | of my knowledge. | |
| | | | | | | |
| | A Contract of the | en | 10 0. | IINTON | <u>OIL COMPANY OF CALIFORNIA DBA</u> U | |
| pproved | erroug | | . 19 Op | erator Sitton | OIL COMMIN OF CHETTORITA DOM | |
| proved | Conservation D | ivision | . 19 Op By | DP. | | |

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

Title

Date

1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever temedial work has been done on a well during which the packer or the tubing have been distructed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.

DEPUTY OIL & GAS INSPECTOR

- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization: Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven down.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

that the previously produced zone shall remain shut in while the zone which was previously shut in it produced.

Production Foreman

April 19, 1996

7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifteen-minute intervals during the first hour thereof, and at hously intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).

RLC/sk1

Title

Commenced at (hour, date) * *