

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office **New Mexico**
Lease No. **079394**
Unit **San Juan 27-5**
14-08-001-950

RECEIVED

APR 3 1958

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 31, 1958

Well No. **30** is located **1140** ft. from **[N]** line and **800** ft. from **[E]** line of sec. **21**

NE Sec. **21**
(¼ Sec. and Sec. No.)

27N
(Twp.)

5W
(Range)

N.M.P.M.
(Meridian)

Blanco M.V. & Undesignated P.C.
(Field)

Rio Arriba
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is **6500** ft.

DETAILS OF WORK


(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

On 3-26-58. Total Depth 3562'.

Ran 87 joints 7 5/8", J-55, 26.40#, Casing (3549') set at 3561' with 50 sacks regular cement, 50 sacks Pozmix, 25# Flocele and 2# Gel, followed with 50 sacks Heat cement.

Held 1000# for 30 minutes.

Top of cement by temperature survey at 2700'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 997**

Farmington, New Mexico

By **Original Signed D. C. Johnston**

Title **Petroleum Engineer**