

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells 11 1: 20

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1140' FNL, 800' FEL, Sec. 21, T-27-N, R-5-W, NMPM

DHC-2617

5. Lease Number
SF-079394

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number
San Juan 27-5 Unit
San Juan 27-5 U #30

9. API Well No.
30-039-07000

10. Field and Pool
Tapacito Pict. Cliffs/
Blanco Mesaverde

11. County and State
Rio Arriba Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☐ Abandonment ☐ Change of Plans
☐ Recompletion ☐ New Construction
☐ Plugging Back ☐ Non-Routine Fracturing
☐ Casing Repair ☐ Water Shut off
☐ Altering Casing ☐ Conversion to Injection
☒ Other - Restimulation and commingle

13. Describe Proposed or Completed Operations

10-9-00 MIRU. ND WH. NU BOP. TOOH w/105 jts 1 1/4" tbg. SDON.
10-10-00 TOOH w/182 jts 2 3/8" tbg & pkr. TIH w/7 5/8" RBP, set @ 1200'. Load hole w/2% KCl wtr. PT RBP, OK. TOOH. ND BOP. Change out well head. NU WH. NU BOP. TIH w/retrieving tool. Latch RBP @ 1200', TOOH. SDON.
10-11-00 TIH w/4 3/4" bit & csg scraper to 5670'. TOOH. TIH w/5 1/2" CIBP, set @ 5470'. Load hole w/60 bbl 2% KCl wtr. PT CIBP to 4100 psi, OK. TOOH. TIH, run CBL-CCL-GR @ 3522-5470', TOC on 5 1/2" lnr @ 4100'. TOOH. TIH, perf Menefee w/1 SPF @ 5242, 5244, 5246, 5248, 5266, 5268, 5270, 5294, 5296, 5298, 5312, 5314, 5340, 5342, 5348, 5350, 5374, 5376, 5378, 5380, 5382, 5412, 5414, 5418, 5420, 5422, 5436, 5438' w/28 0.32" diameter holes total. SDON.
10-12-00 Acidize w/1750 gal 15% HCl. Frac Menefee w/1950 bbl slk wtr, 80,000# 20/40 Brady sd. CO after frac. SDON.
10-13-00 TOOH. TIH w/5 1/2" CIBP & pkr. Set CIBP @ 5160', set pkr @ 4800'. TOOH. TIH, perf Cliff House w/1 SPF @ 5002, 5004, 5006, 5010, 5012, 5014, 5016, 5018, 5020, 5022, 5048, 5050, 5056, 5058, 5060, 5098, 5100, 5102, 5106, 5108, 5110, 5112, 5114, 5116, 5118, 5120, 5122, 5124, 5126, 5128' w/300.32" diameter holes total. Acidize w/25 bbl 15% HCl. Frac Cliff House w/1905 bbl slk wtr, 80,000# 20/40 Brady sd. CO after frac. SDON.
10-14-00 Attempt to release pkr. TIH w/free point. Pipe free @ 4755'. Pkr @ 4793'. Shot hole in frac tbg @ 4785'. TOOH. Release pkr. TOOH. TIH w/CIBP, set @ 4750'. Perf Lewis w/1 SPF @ 4300-4310', 4480-4490', 4610-4620', 4710-4720' w/40 0.32" diameter holes total. TOOH. SDON.

Continued on back

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 11/1/00
no


(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMCCD



10-15-00 TIH to 3400'. Blow well & CO. TOOH. TIH to 3522'. SDON.
10-16-00 TIH, acidize w/2000 gal 10% acetic acid. Frac Lewis w/900 bbl 30# linear gel, 200,000# 20/40 Brady sd. CO after frac.
10-17-00 Blow well & CO.
10-18-00 TOOH. TIH w/7 5/8" RBP, set @ 3450'. PT RBP, OK. Load 7 5/8" csg. PT csg to 500 psi, OK. SDON.
10-19-00 Frac Lewis w/460 bbl 30# linear gel, 175,000# 20/40 Brady sd. CO after frac.
10-20-00 TOOH. TIH w/retrieving tool to 3454'. Blow well & CO.
10-21/22-00 Blow well & CO.
10-23-00 Release RBP @ 3450'. TOOH. TIH w/4 3/4" mill to 4250'. Blow well & CO.
10-24-00 Mill out CIBP @ 4750'. Blow well & CO @ 5100'.
10-25-00 Mill out CIBP @ 5155'. TIH, blow well & CO. Mill out CIBP @ 5470'. TIH, blow well & CO to PBTD @ 5670'.
10-26-00 Blow well & CO. SDON.
10-27/30-00 Blow well & CO.
10-31-00 Blow well & CO. TOOH. TIH w/181 jts 2 3/8" 4.7# J-55 EUE tbgs, landed @ 5643'. (SN @ 5609'). ND BOP. NUW H. RD. Rig released.

Well will produce as a Pictured Cliffs/Mesaverde under DHC-2617