

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas ☒ well ☐ other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, N.M. 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 500'S & 100'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☒

RECEIVED

JUN 30 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

5. LEASE
SF 079403

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 27-5 Unit

8. FARM OR LEASE NAME
San Juan 27-5 Unit

9. WELL NO.
95

10. FIELD OR WILDCAT NAME
Tapacito Pictured Cliffs

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 15, T-27-N, R-5-W

12. COUNTY OR PARISH Rio Arriba 13. STATE New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6610' GL, 6620' DF

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The following plug and abandonment operation was completed on 6-24-82.

- 1) Move on location and rig up.
- 2) Unseated 2 7/8" retrievable packer and T.O.O.H. with 100 joints 1-1/4" tubing.
- 3) Spotted a 30 sx cement plug from 3529 to 2716'.
- 4) Perforated 2 7/8" casing at 172' and circulated a 45 sx cement plug to surface through the casing annulus.
- 5) Cut off well head and erected surface marker.

RECEIVED

DEC 27 1984

OIL CON. DIV.

DIST# 3

Ft.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Mark Munson TITLE Production Engineer

DATE June 29, 1982

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AS AMENDED

DEC 19 1984

Approved as to plugging of the well bore.
Liability under bond is retained until
surface restoration is completed.

NMOCC

*See Instructions on Reverse Side

M. MILLENBACH
AREA MANAGER