5. LEASE

UNITED STATES DEPARTMENT OF THE INTEDIOR

DEPARTMENT OF THE INTERIOR	SF_079403
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
	San Juan 27-5 Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAMF
1. oil gas G	San Juan 27-5 Unit
well gas well other	
2. NAME OF OPERATOR	9. WELL NO. 94
El Paso Natural Gas Company	
3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME
	Tapacito Pictured Cliffs
P.O. Box 289, Farmington, N.M. 87401	11. SEC., T., R., M., OR BLK. AND SURVEY O
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA
AT SURFACE: 850'S, 1600'E	Section 15, T-27-N, R-5-W
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Rio Arriba New Mexico
16 CHECK ADDRODDIATE DOV TO INDICATE NUMBER	14. API NO.
 CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6620-6L
TEST WATER SHUT-OFF	SEIVED \
FRACTURE TREAT	
SHOOT OR ACIDIZE	.002
REPAIR WELL	198? Neport results of multiple completion or zon change on Form 9-330.)
PULL OR ALTER CASING []	change on Form 9-330.)
MULTIPLE COMPLETE	Carlotte Carlotte Carlotte
CHANGE ZONES ABANDON* STORY TO	The state of the s
ABANDON*	
(0010)	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinent	e all pertinent details, and give pertinent dates rectionally drilled, give subsurface locations and t to this work.)*
The following plug and abandonment operation to	was completed on 6-25-82
1) Move on location and rig up.	was completed on 0 25 02.
2) Spotted a 27 sx cement plug over the inter	rval 3535!=2740!
3) Perforated squeeze holes in 2 7/8" casing	at 176' and girgulated
a 52 sx cement plug to surface.	at 170 and circulated
4) Cut off surface pipe and casing.	الرواعة تتر فيشيد بيان
5) Erected surface marker.	DECEIVEM
6) Rigged down and moved off.	
o, ragged down and moved off.	
	DEC 2 71984
	OIL CON. DIV.
	DIET 3
Subsurface Safety Valve: Manu. and Type	DIST. 3
oubsurface safety valve. Manu. and Type	Set @ Ft
18. I hereby certify that the foregoing is true and correct	
SIGNED Mark Manson TITLE Engineer	
signed //www.//www.	DATE June 29, 1982
(This space for Federal or State office	ce use)
	AS AMENDED
APPROVED BY TITLE TOTAL	DATE
••	DEC 2 0 1984
to plugging of the real home NMOCC	DEO & 0 1304
to plugging of the well hore.	

Approved as Approved as to plugging of the well bor Liability under bond is retained until surface restoration is completed.

M. MILLENBACH *See Instructions on Reverse Side AREA MANAGER