

(SUBMIT IN TRIPPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Alamogordo  
Lease No. 07929  
Unit Rincon Unit


SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |          |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |          |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |          |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |          |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |          |
| NOTICE OF INTENTION TO ABANDON WELL.....            | <u>Water Frac.</u>                              | <u>X</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 17, 1958

Well No. 123 is located 990 ft. from INDEX [S] line and 1190 ft. from INDEX [W] line of sec. 13  
SW Sec. 13 27N 7W N.14.P.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Blanco N.V. Rio Arriba New Mexico  
(Field) (County or Subdivision) (State or Territory)



The elevation of the derrick floor above sea level is 6723 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-13-58. Total Depth 5717'. Plug back T.D. 5637'. Water fractured Point Lookout perforated intervals 5326-5416; 5484-5494; 5514-5580; 5602-5656 with 54,000 gallons water and 55,000# sand. BHP Base, max. pr. 3000#, avg. tr. pr. 1800#. I.R. 38.4 BPM. Flush 9500 gallons.

4-13-58. Total Depth 5717'. Temporary Bridge Plug at 5100'. Water fractured Cliff House perforated intervals 4950-4982; 5000-5022 with 40,000 gallons water and 40,000# sand. BHP 3000#, max. pr. 3000#, avg. tr. pr. 2600#. I.R. 38 BPM. Flush 8500 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997  
Farrington, New Mexico

By Original Signature  
Title Petroleum Engineer