

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other ☐

El Paso Natural Gas Company

P.O. Box 4289, Farmington, NM 87499

AT SURFACE: 990' FSL, 1650' FEL, Sec.14,T27N,  
AT TOP PROD. INTERVAL: R6W  
AT TOTAL DEPTH:

SUBSEQUENT REPORT OF:

RECEIVED

JUN 7 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330) 14 1 5 1983

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

# RECEIVED

**OIL COMPANY**

The subject well is to be plugged and abandoned in the following manner:

- 1) Circulate hole w/9.0 ppg mud.
- 2) Spot 50 sk cement plug through existing tubing to cover Pictured Cliffs perforations and fill casing to 50' above top of Fruitland formation (top 3091'). Squeeze 10 sks cement into perforations.
- 3) Perforate 4 squeeze holes @2690' and spot a 50 sk plug to cover Ojo Alamo (top 2569') from 2509'-2690'.
- 4) Perforate 4 squeeze holes @ 175' and circulate 55 sks cement down casing and up through annulus to surface.
- 5) Remove wellhead and install dry hole marker.
- 6) Clean and reseed location.

Set @ 980 Ft.

## Production

**SIGNED**

**TITLE**

Engineer

DATE June 6, 1983

(This space for Federal or State office use)

APPROVED BY

**TITLE**

DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

JAMES F. SIMPSON  
DISTRICT ENGINEER

**NAMOC**

**\*See Instructions on Reverse Side**