
DEC 2 9 1997

OIL & GAS INSPIL Greation Name: SAN JUAN 27-5 UNIT #47 PC Location:TN-27 RG-05 SC-18 UL-K 2 - Federal

> NMOCD Zone: OUTSIDE Hazard Ranking Score:00

Meter Number:72433



RATIONALE FOR RISK-BASED CLOSURE OF PRODUCTION PITS LOCATED OUTSIDE OF THE VULNERABLE ZONE IN THE SAN JUAN BASIN

This production pit location was ranked according to the criteria in the New Mexico Oil Conservation Division's Unlined Surface Impoundment Closure Guidelines and received a ranking score of zero. The estimated depth to groundwater is greater than 100-feet beneath ground surface (bgs), the pit is not in a well head protection area, and there are no surface water bodies within 1,000 horizontal feet of the pit location.

The primary source, discharge to the pit has been removed. There has been no discharge to the pits for at least 4 years and the pits have been closed for at least one year.

Each pit was backfilled with clean soil and graded in a manner to divert precipitation away from the excavated area. Minimal infiltration of rainfall is expected. Any rainfall that does infiltrate the ground surface must migrate through clean backfill before reaching the residual hydrocarbons.

There is no source material at the ground surface, so direct contact of hydrocarbons with livestock and the populous is not likely.

In general, outside of the vulnerable area and alluvial valleys, bedrock material is generally encountered within 20 feet of the ground surface. Bedrock material in the San Juan Basin consists of interbedded sandstones, shales and clays. According to Freeze and Cherry, 1979, the hydraulic conductivity of the bedrock material are as follows:

10⁻⁹ to 10⁻¹³ cm/sec Sandstone 10⁻¹² to 10⁻¹⁶ cm/sec Shale 10⁻¹² to 10⁻¹⁵ cm/sec Clav

Based on this information, the residual hydrocarbons should not migrate to groundwater.


Natural process (bioremediation) are degrading the residual hydrocarbon to carbon dioxide and water and will continue until the source is gone, therefore minimizing any impact to the environment.

Based on the above information, it is highly unlikely that any source material will impact groundwater or ever find an exposure pathway to affect human health and therefore El Paso Field Services Company (EPFS) requests closure of this pit location.



FIEED PIT SITE ASSESSMENT FORM

| GENERAL | Meter: 72433 Location: SAN JUAN 27-5 UNIT #97 PC Operator #: 2999 Operator Name: MERIDIAN P/L District: BLOOMFIELD Coordinates: Letter: K Section 18 Township: 27 Range: 5 Or Latitude Longitude Pit Type: Dehydrator Location Drip: X Line Drip: Other: Site Assessment Date: 5-14-94 Area: 10 Run: 52 | | | | | |
|------------|--|--|--|--|--|--|
| | NMOCD Zone: Land Type: BLM ☒ (1) (From NMOCD State ☐ (2) Maps) Inside ☐ (1) Fee ☐ (3) Outside ☒ (2) Indian | | | | | |
| ASSESSMENT | Wellhead Protection Area: Is it less than 1000 ft from wells, springs, or other sources of fresh water extraction?, or; Is it less than 200 ft from a private domestic water source? (1) YES (20 points) (2) NO (0 points) | | | | | |
| SITE ASS | Horizontal Distance to Surface Water Body Less Than 200 Ft (20 points) | | | | | |
| | (Surface Water Body : Perennial Rivers, Major Wash, Streams, Creeks, Irrigation Canals, Ditches, Lakes, Ponds) Distance to Nearest Ephemeral Stream (1) < 100'(Navajo Pits Only) (2) > 100' | | | | | |
| ίδ | Remarks: 2 PITS ON (SATION) AND DIT TO BE ALCOHOL | | | | | |
| REMARKS | Remarks: 2 PITS ON LOCATION, ONE PIT TOBECLOSED | | | | | |
| REM | PUSHIN' | | | | | |



· 1970年中国建筑的企业。

| | ORIGINAL PIT LOCATION |
|-----------------------|--|
| Z | Original Pit : a) Degrees from North <u>229°</u> Footage from Wellhead <u>64′</u> b) Length : <u>/7′</u> Width : <u>/7′</u> Depth : <u>3′</u> |
| ORIGINAL PIT LOCATION | N 229° |
| REMARKS | Remarks: PHOTOGRAPHS AH-4(23-25)AH-5(1) |
| | TANDEM |
| | |
| | |
| | |
| | |
| | Completed By: |
| | 11. A Naus 5-14-93 |
| | Signature Date |

FIE PIT REMEDIATION/CLOSE E FORM

| GENERAL | Meter: 72433 Location: San Java 27-5 Unit 447 BC Coordinates: Letter: K Section 18 Township: 27 Range: 5 Or Latitude Longitude Date Started: 6-23-94 Area: 10 Run: 52 |
|--------------------|--|
| FIELD OBSERVATIONS | Sample Number(s): MK 17 Sample Depth: 2 Feet Final PID Reading 163 PID Reading Depth 2 Feet Yes No Groundwater Encountered (1) (1) (2) Approximate Depth Feet |
| CLOSURE | Remediation Method: Excavation |
| REMARKS | Remarks: Gray soil EANG lines weren't were not marked EPNG Switcher was with US Hit Sand Stone at 8' Signature of Specialist: Mogan Kileian (SP3191) 04/07/94 |

-2-



FIELD SERVICES LABORATORY ANALYTICAL REPORT PIT CLOSURE PROJECT - Soil

SAMPLE IDENTIFICATION

| | Field ID M 14 27 | | 245506 | | | | |
|---------------------------|-------------------|--|------------|---------------------------|--------|-------|--|
| SAMPLE NUMBER: | | | | | | | |
| MTR CODE SITE NAME: | 72433 | | N/A | | | | |
| SAMPLE DATE TIME (Hrs): | Le - 23- | 4-23-94 N/A | | 1015 | | | |
| SAMPLED BY: | / / 2 | | | A (20/ = 1/ | | | |
| DATE OF TPH EXT. ANAL.: | 6/2 | | | 6/2/1/94 | | | |
| ATE OF BTEX EXT. ANAL.: | | | N/A | | | | |
| TYPE DESCRIPTION: | V G | V G- | | Brown Grey Clay/Sandstone | | | |
| REMARKS: | | | | | | | |
| | | RESULTS | | | | | |
| PARAMETER | RESULT | UNITS | QUALIFIERS | | | | |
| | | | DF | Q | M(g) | V(ml) | |
| BENZENE | | MG/KG | | | | | |
| TOLUENE | | MG/KG | | | | , | |
| ETHYL BENZENE | | MG/KG | | | | | |
| TOTAL XYLENES | | MG/KG | | | | | |
| TOTAL BTEX | | MG/KG | | | | | |
| TPH (418.1) | 287 | MG/KG | | | 2.21 | 28 | |
| HEADSPACE PID | ルコ | PPM | | | | -3. | |
| PERCENT SOLIDS | 88.1 | % | | | | | |
| Surrogate Recovery was at | 1 | 18.1 and BTEX is by EPA Me % for this sample | | was accep | table. | | |

in Water and Soil

Perkin-Elmer Model 1600 FT-IR Analysis Report ******************

94/06/27 15:28

Sample identification ?45506 එ⊍F AND 667/94

Initial mass of sample, g

Volume of sample after extraction, ml 38.000

Petroleum hydrocarbons, ppm 186,880

Net absorbance of hydrocarbons (2930 cm-1) 0.042

