



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office **Santa Fe**
Lease No. **079391**
Unit **San Juan 27-5 Unit**
14-08-001-950

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 30, 1960

Well No. **49(PM)** is located **1090** ft. from **N** line and **800** ft. from **E** line of sec. **18**

NE Sec. **18** **27-N** **5-W** **N.M.P.M.**
(34 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco M.V. & So. Blanco P.C. Ext. **Rio Arriba** **New Mexico**
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is **6564** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding job, cementing points, and all other important proposed work)

Spud date 10-22-60. On 10-22-60 T.D. 133'.
Ran 3 joints 10 3/4", 31.68 # Armo S.W. casing (121') set at 133' w/160
shs. 90-90 Dixie. Held 600 # 30 min.

On 10-28-60, Total Depth 3550'. Ran 93 joints 7 5/8", J-55, 26.4 #, casing
(3537) set at 3549' with 180 shs. reg. cement, 2 % calcium chloride, 1/4 cu.
ft. Strata-Crete "6"/sk. Held 1500 # 30 minutes.

On 10-31-60 Total Depth 5715'.
Ran 54 joints 5 1/2", J-55, 15.5 # liner (2220') set from 3490' to
5710 with 210 shs. regular cement, 1/8 # Floceal/sk., & 4 % Gel, 1/4
cu. ft. fine Gilsomite/sk.

11-1-60 Set Baker Full Bore @ 3383'. Sq. top of liner w/100 shs reg cement, 2 %
calcium chloride. Max & final pr 2000 #. Held 1500 # 30 minutes.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **El Paso Natural Gas Company**

Address **Box 990**
Farmington, New Mexico

By **ORIGINAL SIGNED H.E. McNALLY**
Title **Petroleum Engineer**