


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079392
Unit San Juan 27-5 Unit
14-08-001-950



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Frac</u>	<u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 25, 1957

Well No. 26 (FM) is located 990 ft. from [N] line and 1530 ft. from [E] line of sec. 17

NE Section 17

(¼ Sec. and Sec. No.)

27N

(Twp.)

5N

(Range)

N.M.P.M.

(Meridian)

Wildcat & Blanco

(Field)

Rio Arriba

(County or Subdivision)

New Mexico

(State or Territory)

The elevation of the derrick floor above sea level is 6585 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-17-57. Total Depth 5690'. Plug back T.D. 5680'. Water fractured Point Lookout perforated intervals 5562-76; 5590-5604; 5614-5624; 5646-70 with 77,000 gallons water and 60,000# sand. Breakdown pressure 1450#, maximum pressure 1450#, average treating pressure 1200#. Injection rate 72 bbls./min. Flush 10,000 gallons.

3-17-57. Total Depth 5690'. Temporary Bridge Plug at 5350'. Water fractured Cliff House perforated intervals 5022-32; 5040-53; 5067-86; 5130-42; 5154-70; 5186-5202 with 55,000 gallons water and 55,400# sand. Breakdown pressure 1500#, maximum pressure 3000#, average treating pressure 2000#. Injection rate 60 bbls./min. Flush 9000 gallons.

3-17-57. Total Depth 5690'. Temporary Bridge plug at 3525. Water fractured Pictured Cliffs perforated intervals 3378-3410 with 36,000 gallons water and 26,400# sand. Breakdown pressure 1200#, maximum pressure 1200#, average treating pressure 1200#. Injection rate 52 bbls./min. Flush 6000 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 997

Farmington, New Mexico

By ORIGINAL SIGNED EOW BOB
Title Petroleum Engineer

