


3 - ~~UNIT~~  
1 - ~~L. G. Tracy~~ (SUBMIT IN TRIPLICATE)  
1 - ~~FILE~~



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Indian Agency \_\_\_\_\_  
Flourville  
Allottee Gen. 420  
Lease No. Gen. 4179  
FP Co L-78417

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	Supplementary Report of Well Completion

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

RECEIVED  
JAN 16 1957  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, NEW MEXICO

Indian P 41 Well No. P 41 is located 1306 ft. from [N] line and 1836 ft. from [E] line of sec. 16  
NE 1/4 NE 1/4 16 27 North 3 West E. N. P. M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Wildest Flatted Cliffs Rio Arriba New Mexico  
(County or Subdivision) (State or Territory)

The elevation of the drilled ground above sea level is 7070 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Perf from 6010-32, 6032-42, 6052-52, 6102-32, 6132-32, 6142-42, 6152-42, 6174-76, 6182-42. From 6010-6182 by Dowell w/ 122,500 gal water & 87,000# 20-40 sand. Inj. 670 rubber balls at 25 RPM and decreased to 15. Perf upper Sandstone from 5702-54, 5732-42, 5752-54, 5772-52, 5812-12, 5822-32, 5832-32. Set Entry Bridge Plug @ 5841'. From by Dowell w/ 50,400 gal water and 42,000# 20-40 sand. Used 240 rubber balls at 20 per min. Perf Flatted Cliffs from 3752-70, 3792-52, 3842-54, 3852-52, 3872-52. Set Entry Bridge Plug @ 3902'. From by Dowell w/ 40,800 gal water & 42,000# 20-40 sand. Drugged 140 rubber balls.

Cleaned out to Total Depth. Ran 197 jts 2-1/8" tubing (6192.85') set at 6182.35'.


Completed Well.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be

Company PACIFIC PETROLEUM CORPORATION

Address 405 1/2 West Broadway  
Farmington, New Mexico

By E. A. Ryan  
Title Assistant Division Engineer



2

