


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa Fe
Lease No. 079363
Unit San Juan 28-6 Unit
14-08-001-1051



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA) S. GEOL. SURV.
FARMINGTON, NEW MEXICO
June 16, 1958

Well No. 31 (PW) is located 390 ft. from S line and 890 ft. from W line of sec. 12
SW Sec. 12 27N 6W T.M.P.N.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Blanco & Wildest Rio Arriba New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6000 ft.

DETAILS OF WORK


(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

4-28-58. Total Depth 5604'.

Ran 95 joints 5 1/2", 15.50#, J-55 liner (2257') set from 3342' to 5599' with 125 sacks regular cement, 125 sacks Pozmix, 6 gal, 1/4" Flocele/sk followed by 50 sacks Best cement.

Held 100% for 30 minutes.

Top of cement by temperature survey at 3342'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 397

Farmington, New Mexico

By Original Signed D. C. Johnston

Title Petroleum Engineer